



Products for tomorrow

Headquarter Europe
 MEDER electronic AG
 Friedrich-List Strasse 6
 D-78234 Engen-Welschingen
 Tel.: +49(0)7733-9487-0
 Fax: +49(0)7733-9487-32
 eMail: info@meder.com
 Internet: www.meder.com

Headquarter USA
 MEDER electronic Inc.
 766 Falmouth Rd
 Mashpee, MA 02649
 Phone: +1/ 508-539-0002
 Fax: +1/ 508-539-4088
 eMail: salesusa@meder.com

Reed Relay: B12-1A72-BV625
291 - 9625
Part Number: 3412172625

Dimensions (mm)

Pins: Ø 0,5 mm / L 3,2 ± 0,2 mm

Layout 110 / Pitch 2,54 mm / Top View

Marking

RS-Id. Nr.
 Production-Code-EN60062
 /Factory Code

Coil/Relay Characteristics	Conditions at 20°C	Min.	Typ.	Max.	Units
Coil Resistance		1930	2145	2360	kΩ
Nominal Voltage			12		VDC
Nominal Rated Power			67		mW
Operate Voltage				8,4	VDC
Release Voltage		1,8			VDC

Contact Data 72 (Form A/dry)				
Contact Rating	Any combination of the switching voltage and current must not exceed the given rated power			15 W
Switching Voltage	DC or Peak AC			200 V
Switching Current	DC or Peak AC			1,0 A
Carry Current	DC or Peak AC			1,25 A
Static Contact Resistance (initial)	Measured with Nominal Voltage			150 mΩ
Insulation Resistance	RH 45%	10 ¹²		Ω
Breakdown Voltage		250		VDC
Operate Time, including Bounce	Measured with Nominal Voltage			0,5 ms
Release Time	Measured with no coil suppression			0,2 ms
Capacitance			0,2	pF

Environmental Data				
Insulation Resistance Coil to Contact	RH 45%	10		GΩ
Dielectric Strength Coil to Contact		2,0		kV DC
Shock	½ sine wave, duration 11ms			50 g
Vibration	from 50 - 2000 Hz			20 g
Operating Temperature	10°C/min max. allowable	-20		70 °C
Storage Temperature	10°C/min max. allowable	-25		85 °C
Soldering Temperature	5 sec. at			260 °C
Cleaning				fully sealed
Material of Case				Metal shielding
Sealing Compound				Epoxy resin
Material of Pins				Cu-alloy tinned
Remarks				

Customer	RS Components
----------	----------------------