

ENGLISH

Datasheet

RS Pro Capacitive sensor 25 mm length 134mm SPCO supply voltage 24 V ac/dc IP67

RS Stock No: 413-9641



Product Details

RS Pro capacitive sensor has a detection range of 25 mm long and 24 V ac/dc supply voltage. The high hysteresis and low sensitivity makes this sensor suitable for dirty environments. It comes with PG36 mounting gland, which has rigid and robust features and provides SPDT output type.

Features and Benefits

- IP65 rated
- Fully isolated 5 A changeover relay
- Temperature range from -10 to +55°C
- Diameter of 31 mm, 134 mm long and 1.5 m cable
- · Gland mounting style
- Maximum voltage of 24 V ac



ENGLISH

Specifications:

Body Style	Barrel
Detection Range	25 mm
Dimensions	31 x 134 mm
Housing Material	ABS
IP Rating	IP67
Length	134 mm
Maximum AC Voltage	24 V ac
Maximum DC Voltage	24 V dc
Maximum Operating Temperature	+55°C
Minimum Operating Temperature	-10°C
Mounting Style	PG36 Gland
Output Type	SPCO
Standards Met	RoHS Compliant, CE Certified
Supply Voltage	24 V ac/dc
Switching Current	5 A
Terminal Type	Wire Lead
Indicator	LED