
















# UC-420 / UC-431 UNIVERSAL 3+1 PORT RS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



## Description

Universal PCI providing four RS232 serial ports. Up to 115,200 data transfer rates and the 64 byte deep transmit and 64 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop PC.

Universal PCI is fully compatible with both 3.3Volt and 5Volt PCI slots.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

#### Features

- 4 Port RS232
- Universal PCI
- 64 Byte TX and 64 Byte Rx FIFO
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

### **Options**



UC-420: UNIVERSAL 3+1 PORT RS232

UC-431: UNIVERSAL 3 PORT RS232



#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Vista 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit Editions
- Windows Server 2003 & Windows Server 2008
- Windows 2000

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for all popular programming languages. For more OS support see the 2nd page.























ORDER Description UNIVERSAL 3+1 PORT RS232 **UNIVERSAL 3 PORT RS232** 

Code UC-420

UC-431



EST 1984



UC-420 UC-431



# UNIVERSAL 3+1 PORT RS232

UC-420 / UC-431: Full Specification

oc-420 / oc-451. Tuli specification	
Ports	4 Port RS232
Connector	DB9 connector (9 Pin Male)
FIFO size	64 Tx, 64 Rx
Signal Strength	EIA - RS232 Standard (+/- 12V open circuit)
Operating Distance	EIA - RS232 Standard
, -	
Baud Rate	Up to 115,200
Data Bits	5,6,7 or 8
Parity	Odd, Even, None, Mark or Space
Stop Bits	1, 1.5 or 2
Flow Control	RTS/CTS DSR/DTR XON/XOFF
Tx/Rx Modes	Point to Point
OS Compatibility	Windows Vista 32 bit and 64 bit Editions
	Windows Server 2008 Windows Server 2003 32 bit and 64 bit Editions
	Windows XP 32 bit and 64 bit Editions
	Windows 2000
BUS	PCI 3.0
Other Approvals	IEEC CB Scheme METL VCCI WEEE FCC compliant
Microsoft Approvals	Microsoft Certified Gold Partner
	Windows XP 32 bit & 64 bit Windows Server 2003
	Windows Server 2008
PCB Layers	4
Power Consumption	210mA @ 5V, 60mA @ 12V
Weight	0.150Kg
Size	65 x 120 mm
Packaging	Installation CD including manual, Microsoft signed drivers & utilities
Card	UNIVERSAL 3+1 PORT RS232
	1 Port on Fly lead (UC-420)
Warranty	Lifetime (online registration required)
Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
	stan who work in and alongside the Product Development leam
OEM option	Available for bulk buy OEM
Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume
	Ports Connector FIFO size Signal Strength Operating Distance  Baud Rate Data Bits Parity Stop Bits Flow Control Tx/Rx Modes  OS Compatibility  BUS Other Approvals Microsoft Approvals  PCB Layers Power Consumption Weight Size Packaging Card  Warranty Support  OEM option Made In