



WOYR8.E312400
Switches, Appliance and Special Use Certified for Canada - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Switches, Appliance and Special Use Certified for Canada - Component

[See General Information for Switches, Appliance and Special Use Certified for Canada - Component](#)


HONEYWELL (CHINA) CO LTD
 NO 430 LI BIN RD ZHANG JIANG
 HI-TECH PUDONG NEW AREA
 201203 SHANGHAI, CHINA

E312400

Investigated to CAN/CSA-C22.2 No. 61058-1

Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Pol/	Endurance		IP	Dis (mm)	SPCA	Std. Ed.
						Thr/ Cir	30C cycle	55C cycle				
Appliance and special use switches												
V15W11												
GP	5	125	50-60	T85	1/2-1.2	10K	10K	67	full 0.5	6A, 6B	2005-09-30	
GP	5	250	50-60	T85	1/2-1.2	10K	10K	67				
R	5	30	DC	T85	1/2-1.2	10K	10K	67				
GP	0.1	125	50-60	T85	1/2-1.2	10K	10K	67				
GP	0.1	250	50-60	T85	1/2-1.2	10K	10K	67				
R	0.1	48	DC	T85	1/2-1.2	10K	10K	67				
hp	1/10	125	50-60	T85	1/2-1.2	10K	10K	67				
hp	1/10	250	50-60	T85	1/2-1.2	10K	10K	67				
GP	10.1	125	50-60	T85	1/2-1.2	10K	10K	67				
GP	10.1	250	50-60	T85	1/2-1.2	10K	10K	67				
R	0.5	125	DC	T85	1/2-1.2	10K	10K	67				
R	0.25	250	DC	T85	1/2-1.2	10K	10K	67				

Marking: Company name or tradename "HONEYWELL", "MICRO", "MICROSWITCH", catalog, model or part number, electrical ratings and

Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Investigated to CSA-C22.2 No. 55

Cat. No.	Amps	Volts	Hz	Load	Endurance	Temp C	POL/ THR	Per Pole/ Circuit Code	SPCOA
V15B08	10.1	125	50/60	GP	6K	125	1/2	-/A	-
	10.1	250	50/60	GP	6K				
	-	250	50/60	1hp	6K				
V15H10	10	125	60	GP	100K	150	1/2 or 1/1	-/A	Note 3
	10	250	60	GP	100K				
	9.8	125	60	1/2hp	100K				

	4.9	250	60	1/2hp	100K				
	1	30	DC	R	100K				
V15H16	9.8	125	60	1/2hp	6K	150	1/2 or 1/1	-/A	Note 3
	4.9	250	60	1/2hp	6K				
	16	125	60	GP	6K				
	16	250	60	GP	6K				
V15H22	16	125	60	1hp	6K	150	1/2 or 1/1	-/A	Note 3
	8	250	60	1hp	6K				
	22	125	60	GP	6K				
	22	250	60	GP	6K				
V15S05	5	125	60	GP	6K	85	1/2 or 1/1	-/A	Note 3
	5	250	60	GP	6K				
	3	125	60	1/10hp	6K				
	1.5	250	60	1/10hp	6K				
	0.1	48	DC	R	6K				
V15T10	11	125	60	GP	6K	125	1/2 or 1/1	-/A	Note 3
	11	250	60	GP	6K				
	0.5	125	DC	GP	6K				
	0.25	250	DC	GP	6K				
	4	125	60	L	12K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
V15T16	16	125	60	GP	6K	125	1/2 or 1/1	-/A	Note 3
	16	250	60	GP	6K				
	9.8	125	60	1/2hp	6K				
	4.9	250	60	1/2hp	6K				
V15T22	22	125	60	GP	6K	125	1/2 or 1/1	-/A	Note 3
	22	250	60	GP	6K				
	16	125	60	1hp	6K				
	8	250	60	1hp	6K				
ZD	0.1	125	60	GP	6K	85	1/2	-/A	-
	0.1	250	60	GP	6K				
	0.1	48	DC	GP	6K				
	3	12	DC	GP	6K				
ZM10, ZM101	0.1	125	60	GP	6K	125	1/2	-/A	--
	0.1	250	60	GP	6K				
	0.1	48	DC	R	6K				
ZM50	5	125	60	GP	6K	125	1/2	-/A	-
	5	30	DC	-	6K				
	5	250	60	GP	6K				
	-	125	60	1/8hp	6K				
	-	250	60	1/8hp	6K				
ZM501	5	125	60	GP	6K	125	1/2	-/A	Note A1


	5	250	60	GP	6K				
	-	125	60	1/8hp	6K				
	-	250	60	1/8hp	6K				
	-	-	-	GP	-				
ZM90	10.1	125	60	GP	6K	125	1/2	-/A	--
	10.1	250	60	GP	6K				
	5.8	125	60	1/4hp	6K				
	2.9	250	60	1/4hp	6K				
ZM901	10.1	125	60	GP	6K	125	1/2	-/A	Note A1
	10.1	250	60	GP	6K				
	-	125	60	1/4hp	6K				
	-	250	60	1/4hp	6K				
ZM92	12	125	60	GP	6K	125	1/2	-/-	A7
	12	250	60	GP	6K				
ZW10 f/b 15 or 20									
	0.1	125	60	GP	6K	120	1/2	-/A	-
	0.1	250	60	GP	6K				
	0.1	48	DC	R	6K				
ZW10 f/b 90,91 or 92									
	0.1	250	60	GP	6K	105	1/2	-/A	--
	0.1	125	60	GP	6K				
	0.1	48	DC	R	6K				
ZW50 f/b 15 or 20									
	5	250	60	GP	6K	120	1/2	-/A	--
	5	125	60	GP	6K				
ZW50 f/b 90, 91 or 92									
	5	125	60	GP	6K	105	1/2	-/A	-
	5	250	60	GP	6K				
ZW90	10.1	125	60	GP	6K	125	1/2	-/A	-
	10.1	250	60	GP	6K				
	-	125	60	1/4hp	6K				
	-	250	60	1/4hp	6K				
	5	125	60	GP	6K				
	5	250	60	GP	6K				
	-	125	60	1/8hp	6K				
	-	250	60	1/8hp	6K				
	0.1	125	60	GP	6K				
	0.1	250	60	GP	6K				
	0.1	48	DC	GP	6K				
ZW90 (L)	10.1	125	60	GP	6K	85	1/2	-/A	-
	10.1	250	60	GP	6K				
	-	125	60	1/4hp	6K				
	-	250	60	1/4hp	6K				

	5	125	60	GP	6K				
	5	250	60	GP	6K				
	-	125	60	1/8hp	6K				
	-	250	60	1/8hp	6K				
	0.1	125	60	GP	6K				
	0.1	250	60	GP	6K				
	0.1	48	DC	GP	6K				
ZX	0.1	48	DC	-	6K	85	1/2	-/A	-
	0.1	125	60	GP	6K				
	1	125	60	GP	6K				
	3	125	60	GP	6K				

Note A1 - These switches may also employ brass quick-connect terminals

Note A7 - The nonstandard quick connect terminals are intended for solder use only.

Marking: Company name or tradename "HONEYWELL", "MICRO", "MICROSWITCH", catalog, model or part number, electrical ratings and

Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2011-08-26

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

