



PVC light-weight hose with rigid PVC spiral, for suction and ducting of air, fumes, chips, dusts, textile filaments, ventilation and for electrical cables protection. Self-extinguishing in compliance with UL 94 V2.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-10°C +65°C
14°F +149°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE



SELF-EXTINGUISHING

UL94 V2

Ø I.D.	Ø I.D.	Ø O.D.	WALL THICKNESS	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	mm	g/m	mm	bar	mm		m	
5/16	8	12	0.7	2	50	8		5.2	right	30	IN STOCK
3/8	10	14.6	0.7	2.3	70	10		5.5	right	30	IN STOCK
	12	16.4	0.7	2.2	75	12		5.6	right	30	IN STOCK
	14	18.8	0.7	2.4	90	14		6	right	30	IN STOCK
	15	19.6	0.7	2.3	95	15		6	right	30	IN STOCK
5/8	16	20.6	0.7	2.3	100	16		6.2	right	30	IN STOCK
	18	22.6	0.7	2.3	110	18		6.5	right	30	IN STOCK
3/4	19	23.6	0.7	2.3	118	19		7	right	30	IN STOCK
	20	24.6	0.7	2.3	125	20		6.7	right	30	IN STOCK
	22	27.6	0.7	2.8	150	22		7.2	right	30	IN STOCK
1	25	30.6	0.7	2.8	180	25		7.2	right	30	IN STOCK
	28	33.6	0.8	2.8	210	28		7.4	right	30	IN STOCK
	30	36	0.8	3	230	30		7.4	right	25	IN STOCK
1 1/4	32	38	0.8	3	240	32		8	right	25	IN STOCK
	35	41	0.8	3	280	35		8.2	right	25	IN STOCK
1 1/2	38	44.4	0.8	3.2	310	38		8.2	right	25	IN STOCK
	40	46.6	0.9	3.3	330	40		8.5	right	25	IN STOCK
1 3/4	45	51.8	0.9	3.4	380	45		9.5	right	25	IN STOCK
2	50	57.2	0.9	3.6	430	50		10	right	25	IN STOCK
	60	68	0.9	4	560	60		11.3	right	25	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.