



承认书

SPECIFICATION FOR APPROVAL

客 户 CUSTOMER	F200
品 名 DESCRIPTION	DC FAN
机 种 MODEL	D3110N-04W-B06
单 号 PARTNO	
提出日期 DATE	2016 年 06 月 17 日
版 本 EDITION	1.0

制作确认 MADE APPEOVE
制作:
检查:
核准:

客户确认 CUSTOMER APPROVE
承认:
核准:
日期:

1.0: 一般规格 (General Specification)

项目 (Item)		规格/条件 (Specification/Condition)	
1	型号 (Model No.)	D3110N-04W-B06	
2	外型尺寸 (Outline Dimension)	80*80*25mm	
3	工作电压 (Operating Voltage)	DC 10-14V	
4	额定电压 (Rated voltage)	DC 12V	
5	启动电压 Starting Voltage	DC ≤12V on/off	
6	额定电流 (Rated current)	0.20A (MAX 0.25A)	a. 额定电压 (Rated voltage) b. 25°C 65% RH c. After testing for 5 minutes
7	消耗功率 (Power consumption)	4.8W (MAX5.20W)	
8	转速 (Speed)	4000±10%RPM	
9	最大风量: (Max Airflow)	51.71CFM	a. 额定电压 (Rated voltage) b. AMCA 标准 (Standard) c. 额定电流 (Rated current)
	最大静压: (Air Static Pressure)	6.27mmH2O	
10	噪音标准 (Noise Level)	≤42.97dB	a. 额定电压 (Rated Voltage) b. 无响室 (Non-Echo Chamber) c. 标准 (Standard): CNS 8753 / ISO 3744 d. Test Condition : ISO 7779 e. 距离 (Distance): 1.0 M
11	Life expectancy (期望寿命)	50000Hrs 25°C	MTTF (Mean Time To Failure) Conf. Level 90%
12	扇叶数 (No. of Blade)	7 叶	
13	极数 (No. of Pole)	4 极	
14	运转方向 (Rotating Direction)	逆时针	
15	锁住保护 Lock Protection	<input type="checkbox"/> 无 NO	
16	极性保护 Polarity Protection	<input type="checkbox"/> 无 NO	
17	过压保护 (Overvoltage protection)	<input type="checkbox"/> 无 NO	
18	过流保护 (Overcurrent protection)	<input type="checkbox"/> 无 NO	
19	恒速功能 fixed constant speed Function	<input type="checkbox"/> 无 NO	
20	PWM 功能 PWM function	<input type="checkbox"/> 无 NO	
21	PQ 曲线	<p>■ Characteristic Curves (特性曲线)</p> 	

2.0:主要材料/零件规格 (Main Materials/parts Specification)

材料/零件 (Materials/parts)		规格 (Specification)	
1	塑料材料/扇叶 外框 (Plastic Material/Blade, Housing)	PBT 黑色方框 7 叶 (环保防火)	
2	轴承 (Bearing Type)	滚珠轴承 (Ball Bearing)	
3	引线 (Lead Wire)	UL1007*24#L1=250mm 红(正极)、黑 (负极)	
4	端子 (Connector)	无端	
		黑	红
		GND	VCC

3.0 电性规格 (Electrical Specifically)

1	绝缘阻抗 Insulation Resistance	10M Ω /裸线与外框间测量, 500VDC/min 10M Ω /between unshackled wire and frame at 500VDC/min
2	绝缘耐压 Dielectric Strength	5Ma Max. /导线与外框间测量, 500VAC/min 5Ma Max. /Measured between lead wire(+)and frame at 500VAC/min
3	防水等级 Waterproof level	IP X0

4.0 环境测试 (Environmental Specification)

1	运转温/湿度范围 Operating Temp .Range	温度/Temperature:-10 $^{\circ}$ C~+60 $^{\circ}$ C 湿度/Humidity:35%~85%RH
2	保存温/湿度范围 Storage Temperature	温度/Temperature:-40 $^{\circ}$ C~+70 $^{\circ}$ C 湿度/Humidity:35%~85%RH
3	耐湿性 Humidity	电气规格依据 MIL-STD 202F Method 103B 湿度: 95%RH 温度: 40 \pm 2 $^{\circ}$ C
4	热冲击 Thermal Shock	电气规格依据 MIL-STD 202F Method 107D Per MIL-STD 202F Method 107D, Condition D
5	绝缘阶段 Insulation Shock	UL: A 种 UL: Class A
6	包装耐振动试验 Packing Vibration Test	包装后, XYZ 三方向施 1.1G load vibration test for 30min .No serious damage
7	包装耐冲击试验 Packing Shock Proof Test	捆包后, 高 60 公分, 1 棱角 3 边 6 面自然落下, 无严重损坏. 1corner, 3edges, 6faces natural drop from 60cm high packing No serious damage

注意事项 (NOTES)

1. Before use, make sure the supply voltage to meet the use of the product range, line-powered load exceeds the maximum power consumption of this product 120%. And the voltage is stable without clutter
(使用前, 确认供电电压能满足本产品的使用范围, 供电电路负载超过本产品的最大功耗的120%。且电压是稳定不含杂波干扰)
2. Please when ventilator circular telegram normal work do not use the hand to bump touches fan blade border
(请在风扇通电正常运转时不要用手碰触扇叶边沿)
3. Please do not touch the impeller and never carry the fan the lead wires. The bearings and the lead wires may be damaged. Additionally, static electricity may damage the intemal circuits of the fan
(请不要碰触扇叶和拉扯线材, 以免损坏轴承及导线。此外, 静电可能损坏内部的风扇组件)
4. Please do not use the fan in the environment of corrosive gas or liquid.
(请不要将风扇置于腐蚀的气体 and 液体内)
5. Please do not store the an in the environmet of high humidity. Please avoid storage of the fan over 6months. For long term storage, please connect power to the fan shortly every 6 months even through the fan is stored in room temperature.
(请不要将风扇储存在高湿度的环境中, 请尽量避免将风扇储存期超过6个月。如果要长期储存, 请将其在室温的环境下。且每隔6个月须上电源让风扇短时间运转。)

