

76x30 mm

San Ace B76 9BD type   



General Specifications

- Material Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-1)
- Expected life See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60°C, rated voltage)
- Motor protection function Locked rotor burnout protection, Reverse polarity protection
For details, please refer to p. 547.
- Dielectric strength 50/60 Hz, 500 VAC, for 1 minute (between lead wire conductors and frame)
- Insulation resistance 10 MΩ or more with a 500 VDC megger (between lead wire conductors and frame)
- Sound pressure level (SPL) At 1 m away from the air inlet
- Storage temperature -30 to +70°C (Non-condensing)
- Lead wire  Red  Black or Blue  Sensor Yellow
- Mass 100 g

Specifications

The models listed below have pulse sensors.

Model no.	Rated voltage [V]	Operating voltage range [V]	Rated current [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min] [CFM]	Max. static pressure [Pa] [inch H₂O]	SPL [dB (A)]	Operating temperature [°C]	Expected life [h]
109BD12HC2	12	10.2 to 13.8	0.37	4.44	3000	0.36 12.7	151.9 0.61	41.5	-20 to +60	40000/60°C
109BD12FC2			0.27	3.24	2600	0.31 10.9	98 0.394	37	-20 to +70	
109BD12MC2			0.14	1.68	2100	0.25 8.8	58.8 0.236	32.5	-20 to +70	
109BD24HC2	24	20.4 to 27.6	0.17	4.08	3000	0.36 12.7	151.9 0.61	41.5	-20 to +60	40000/60°C
109BD24FC2			0.14	3.36	2600	0.31 10.9	98 0.394	37	-20 to +70	
109BD24MC2			0.1	2.4	2100	0.25 8.8	58.8 0.236	32.5	-20 to +70	

The following sensor and control options are available for selection.


Available for all models.  

Differs according to the model. Refer to the table on p. 561. 

Airflow - Static Pressure Characteristics


109BD12HC2 With pulse sensor

Operating voltage range




109BD12FC2 With pulse sensor

Operating voltage range



109BD12MC2 With pulse sensor

Operating voltage range




Airflow - Static Pressure Characteristics

109BD24HC2 With pulse sensor


109BD24FC2 With pulse sensor

109BD24MC2 With pulse sensor


Operating voltage range






Operating voltage range



Operating voltage range



Dimensions (unit: mm)



DC

Blower 76 mm