

Data sheet | Item number: 762-6202/8000-001

Touch Panel 600; 14.5 cm (5.7"); 640 x 480 pixels; 2 x ETHERNET, 2 x USB,
Audio; Visu Panel



www.wago.com/762-6202/8000-001



Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

PIO2 hardware configuration

- 2 x ETHERNET port for connecting to field devices and the engineering tool
- 2 x USB port for optional connection of a USB stick, mouse or keyboard
- Audio interface for connecting a headphone or loudspeaker

Data

Technical data

Display diagonal	14.5 cm (5.7 inches)
Display	Resistive touchscreen (black front)
Display colors	262,000 colors

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Graphics resolution	(640 x 480) px
Contrast ratio	300:1
Viewing angle (horizontal/vertical)	80° / 80°
Brightness	630 cd/m ²
Visualization	Web server Web-Visu Webserver Web Visu
ETHERNET protocols	DHCP DNS FTP FTPS HTTP HTTPS SSH
Communication	EtherNet/IP™ Adapter (slave), library for <i>e!RUNTIME</i> (prerequisite: <i>e!RUNTIME</i> PLC 600 license) Modbus TCP Master/Slave (prerequisite: <i>e!RUNTIME</i> PLC 600 license) EtherCAT Master, requires an additional license (prerequisite: <i>e!RUNTIME</i> PLC 600 license) BACnet/IP, requires an additional license (prerequisite: <i>e!RUNTIME</i> PLC 600 license)
Operating system	Real-time Linux (with RT-Preempt patch)
Processor	ARM® Cortex® A9 Quadcore 1.0 GHz
Programming environment	<i>e!COCKPIT</i> (based on CODESYS V3)
Main memory (RAM)	2,048 MB
Internal memory (flash)	4096 MB
Program memory	32 MB
Data memory	128 MB
Type of memory card	microSD (max. 2 GB); microSDHC (max. 32 GB)
Indicators	Three-color LED (red, green, blue)
Controls	Resistive touch panel; 2 capacitive keys; proximity sensor
Supply voltage	24 VSELV DC (18 ... 31.2 V); with reverse voltage protection
Operating power	6.8 W, without USB load; 11.8 W, with USB load

Connection data

Connection technology: communication/fieldbus	Modbus TCP: 2 x RJ-45; 2 x USB 2.0 host (type A)
Connection technology: supply	1 x included female connector (734-103) with three CAGE CLAMP® connections

Subject to changes. Please also observe the further product documentation!



Physical data

Width	172 mm / 6.772 inches
Height	163 mm / 6.417 inches
Depth	58 mm / 2.283 inches
Panel cutout (W x H)	(157 x 148) mm

Mechanical data

Weight	843 g
--------	-------

Environmental requirements


Ambient temperature (operation)	-20 ... +55 °C (when mounted vertically; -20 ... +50 °C, other mounting positions)
Surrounding air temperature (storage)	-20 ... +80 °C
Protection type	IP65
Note on protection type	IP65 (front side); IP20 (rear side), per EN 60529
Relative humidity (without condensation)	90 %
Mounting type	Clamping elements (included) or VESA mount (4 x M4x8)

Commercial data

ETIM 8.0	EC001414
ETIM 7.0	EC001414
PU (SPU)	1 Stück
Packaging type	box
Country of origin VKOrg Germany	DE
GTIN	4055143839471
Customs tariff number VKOrg Germany	84714100000

Approvals / Certificates

Country specific Approvals

Logo	Approval	Additional Approval Text	Certificate name
	EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	EAC RU C-DE.AM02. B.00087 /19

Ship Approvals

Subject to changes. Please also observe the further product documentation!


WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Logo	Approval	Additional Approval Text	Certificate name
	DNV DNV Germany GmbH	DNVGL-CG-339,Dec.2019	TAA00001FS

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

Compatible products

Mounting

Mounting accessories

Item no.: 762-9001 eDISPLAY7300T ; Clamping elements (4 pieces)	www.wago.com/762-9001
---	--

Software

Software applications



Item no.: 2759-208/211-1000 Library MTP; Single License; Online activation	www.wago.com/2759-208/211-1000
--	--

Memory card

Memory card

Item no.: 758-879/000-3102 Memory Card SD Micro; 2 GByte	www.wago.com/758-879/000-3102
--	--

Item no.: 758-879/000-3108 Memory Card SD Micro; pSLC-NAND; 8 GB; Temperature range: -40 to 90°C	www.wago.com/758-879/000-3108
--	--

Downloads

Documentation

Manual

WAGO Touch Panel 600 Marine Line	V 1.5.0 2022 年5月24 日	pdf 2.4 MB	Download
-------------------------------------	-------------------------	---------------	----------

Bid Text

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



762-6202/8000-001 X81 - Datei	2019 年2月19日	xml 6.0 kB	Download
----------------------------------	-------------	---------------	----------

762-6202/8000-001 docx - Datei	2019 年1月4日	docx 22.6 kB	Download
-----------------------------------	------------	-----------------	----------

Tutorial

Establish connection to a controller using SSH In this video we are demonstrating how to establish a SSH connection with a controller using for example PuTTY to be able to work with the LINUX console. Contents: 0:21 Download and install the SSH client; 0:40 Establish the SSH connection; 0:50 Log on to the Controller	1.0 2017 年8月5日	mp4 29.0 MB	Download
--	-------------------	----------------	----------

System Description

Touch Panel 600, system description		pdf 151.9 kB	Download
-------------------------------------	--	-----------------	----------

Additional Information

WAGO OPC UA Server	V 1.1.0 2021 年1月28日	pdf 1.2 MB	Download
--------------------	------------------------	---------------	----------

Engineering-Software

e!COCKPIT

e!COCKPIT Register at no cost and test our engineering software for 30 days.	V 1.10 2021 年9月27日	zip 3.0 GB	Download
---	-----------------------	---------------	----------

Configuration and Commissioning Software

WAGUpload WAGUpload is a stand-alone PC software for transferring, backing up and restoring PLC applications on WAGO 750 Series controllers.	1.15.0.0 2022 年2月2日	zip 11.7 MB	Download
---	------------------------	----------------	----------

Runtime Software

Firmware

Image Update (SD Karte) TP 600 WAGO_FW0762-4xxx_V030720_IX19_SP3_I	V 19 SP3 2022 年4月19日	zip 165.6 MB	Download
---	-------------------------	-----------------	----------

WUP Update (WAGUpload Tool) TP 600

Subject to changes. Please also observe the further product documentation!



WAGO_FW0762-4xxx_V030720_IX19_SP3_W

V 19 SP3
2022 年4月19日

zip
162.2 MB

[Download](#)

CAD/CAE-Data

CAD data

2D/3D Models 762-6202/8000-001

[URL](#)

[Download](#)

CAE data

ZUKEN Portal 762-6202/8000-001

[URL](#)

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 762-6202/8000-001

[URL](#)

[Download](#)

Touch Panel 600; 14.5 cm (5.7"); 640 x 480 pixels; 2 x ETHERNET, 2 x USB, Audio;
Visu Panel

Installation Notes

Product family

Marine Line

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.