

Single Phase Rectifier Bridge, 1.9 A


2KBB

FEATURES

- Suitable for printed circuit board mounting
- Leads on standard 2.54 mm (0.1") grid
- Compact construction
- High surge current capability
- Polarized package
- Equivalent to standard DIN parts
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

PRODUCT SUMMARY

| | |
|-----------|---------------------|
| I_O | 1.9 A |
| V_{RRM} | 50 V to 1000 V |
| Package | 2KBB |
| Circuit | Single phase bridge |

DESCRIPTION

A 1.9 A single phase diode bridge rectifier assembly consisting of four silicon diodes in a plastic encapsulation, intended for general applications in industrial and consumer equipment.

MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL | CHARACTERISTICS | VALUES | UNITS |
|-----------|-----------------|-------------|------------------|
| I_O | | 1.9 | A |
| | T_C | 45 | °C |
| I_{FSM} | 50 Hz | 50 | A |
| | 60 Hz | 52 | |
| I^2t | 50 Hz | 17.7 | A ² s |
| | 60 Hz | 16.1 | |
| V_{RRM} | | 100 to 1000 | V |
| T_J | | -40 to 150 | °C |

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS AND APPLICATION DATA

| CROSS REFERENCE | | V_{RRM}, V_{RSM} MAXIMUM PEAK REVERSE VOLTAGE $T_J = 15\text{ °C}$ (V) | I_{RM} TYPICAL PEAK REVERSE CURRENT PER DIODE AT RATED V_{RRM} (μ A) | | APPLICATION DATA (SEE FIGURE 3) | | |
|-----------------|-----------|--|---|-----------------------|--|---|--|
| PART NUMBER | DIN CODE | | $T_J = 25\text{ °C}$ | $T_J = 150\text{ °C}$ | V_{RMS} MAXIMUM RECOMMENDE D AC SUPPLY VOLTAGE (V) | C_{MAX} MAXIMUM LOAD CAPACITANCE (μ F) | R_{MIN} MINIMUM SOURCE RESISTANCE (Ω) |
| | | | | | | | |
| VS-2KBB05 | B20C1500 | 50 | 10 | 500 | 20 | 7000 | 0.3 |
| VS-2KBB10 | B40C1500 | 100 | 10 | 500 | 40 | 5000 | 0.5 |
| VS-2KBB20 | B80C1500 | 200 | 10 | 500 | 80 | 3300 | 0.8 |
| VS-2KBB40 | B125C1500 | 400 | 10 | 500 | 125 | 1600 | 1.5 |
| VS-2KBB60 | B250C1500 | 600 | 10 | 500 | 250 | 1200 | 2.5 |
| VS-2KBB80 | B380C1500 | 800 | 10 | 500 | 380 | 800 | 3.0 |
| VS-2KBB100 | B500C1500 | 1000 | 10 | 500 | 500 | 600 | 5.0 |

Note

- For PIN configuration - ~ ~ + add "R" to end of part number, e.g. 2KBB05R (see also dimensions for details - link at the end of datasheet)



| FORWARD CONDUCTION | | | | | |
|--|---------------------|--|--|------------|---------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VALUES | UNITS |
| Maximum DC output current | I_O | $T_C = 45\text{ }^\circ\text{C}$, resistive and inductive load | | 1.9 | A |
| | | $T_C = 45\text{ }^\circ\text{C}$, capacitive load | | 1.5 | |
| Maximum peak one cycle, non-repetitive surge current | I_{FSM} | $t = 6\text{ ms}$ | Following any rated load condition, and with rated V_{RRM} applied following surge | 50 | A |
| | | $t = 5\text{ ms}$ | | 52 | |
| Maximum I^2t for fusing, initial $T_J = T_J$ maximum | I^2t | $t = 10\text{ ms}$ | Rated V_{RRM} applied following surge, initial $T_J = 150\text{ }^\circ\text{C}$ | 12.5 | A^2s |
| | | $t = 8.3\text{ ms}$ | | 11.3 | |
| | | $t = 10\text{ ms}$ | | 17.7 | |
| | | $t = 8.3\text{ ms}$ | | 16.1 | |
| Maximum $I^2\sqrt{t}$ capability for fusing | $I^2\sqrt{t}^{(1)}$ | $t = 0.1\text{ to }10\text{ ms}$, V_{RRM} following surge = 0 | | 177 | $A^2\sqrt{s}$ |
| Maximum peak forward voltage per diode | V_{FM} | $I_O = 1.9\text{ A}$ (3.0 A_{pk}) | | 1.1 | V |
| Operating frequency range | f | | | 40 to 2000 | Hz |

Note

(1) I^2t for time $t_x = I^2\sqrt{t} \times \sqrt{t_x}$

| THERMAL AND MECHANICAL SPECIFICATIONS | | | |
|--|----------------|------------|------------------|
| PARAMETER | SYMBOL | VALUES | UNITS |
| Operating junction and storage temperature range | T_J, T_{Stg} | -40 to 150 | $^\circ\text{C}$ |
| Approximate weight | | 4 | g |
| | | 0.14 | oz. |



Fig. 1 - Average (DC) Output Current vs. Maximum Allowable Ambient Temperature



Fig. 2 - Maximum Non-Repetitive Surge Current vs. Pulse Train Duration ($f = 50\text{ Hz}$)




Fig. 3 - Minimum Required Source Resistance vs. RMS Supply Voltage and Load Capacitance



Fig. 4 - Maximum Switch-On Surge Current vs. Surge Duration

CIRCUIT CONFIGURATION



| LINKS TO RELATED DOCUMENTS | |
|----------------------------|--|
| Dimensions | www.vishay.com/doc?95328 |

2KBB

DIMENSIONS in millimeters (inches)



Note

- For PIN configuration - ~ ~ + add "R" to end of part number



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.