



SITOP PSU6200/1AC/DC48V/10A

SITOP PSU6200 48 V/10 A stabilized power supply input: 120/230 V AC
output: 48 V DC/10 A with diagnostic interface

Input	
type of the power supply network	1-phase AC or DC
supply voltage at AC	
• minimum rated value	120 V
• maximum rated value	240 V
• initial value	85 V
• full-scale value	264 V
supply voltage	
• at DC	110 ... 240 V
input voltage	
• at DC	85 ... 275 V
design of input wide range input	Yes
overvoltage overload capability	300 V AC for 30 s
operating condition of the mains buffering	at $V_{in} = 230$ V
buffering time for rated value of the output current in the event of power failure minimum	25 ms
operating condition of the mains buffering	at $V_{in} = 230$ V
line frequency	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	4.3 A
• at rated input voltage 230 V	2.3 A
current limitation of inrush current at 25 °C maximum	11 A
fuse protection type	10 A
• in the feeder	Circuit breaker from 6 A characteristic B to 16 A characteristic C or circuit breaker 3RV2011-1HA10 (setting 8A) or 3RV2711-1HD10 (UL 489)
Output	
voltage curve at output	Controlled, isolated DC voltage
number of outputs	1
output voltage at DC rated value	48 V
output voltage	
• at output 1 at DC rated value	48 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.3 %
• on slow fluctuation of ohm loading	0.2 %
residual ripple	

<ul style="list-style-type: none"> • maximum 	70 mV
<ul style="list-style-type: none"> • typical 	20 mV
voltage peak	
<ul style="list-style-type: none"> • maximum 	40 mV
<ul style="list-style-type: none"> • typical 	20 mV
adjustable output voltage	48 ... 56 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer; max. 480 W (576 W up to 45°C)
display version for normal operation	Green LED for 48 V OK
type of signal at output	Electronic contact (NO contact, contact rating 30 V DC/0.1 A) for DC O.K. or diagnostic interface
behavior of the output voltage when switching on	Overshoot of $V_{out} < 2\%$
response delay maximum	0.5 s
voltage increase time of the output voltage	
<ul style="list-style-type: none"> • typical 	200 ms
output current	
<ul style="list-style-type: none"> • rated value 	10 A
<ul style="list-style-type: none"> • rated range 	0 ... 10 A; 12 A up to +45°C; +60 ... +70 °C: Derating 3%/K
supplied active power typical	480 W
short-term overload current	
<ul style="list-style-type: none"> • on short-circuiting during the start-up typical 	15 A
<ul style="list-style-type: none"> • at short-circuit during operation typical 	15 A
product feature	
<ul style="list-style-type: none"> • bridging of equipment 	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	95.8 %
power loss [W]	
<ul style="list-style-type: none"> • at rated output voltage for rated value of the output current typical 	21 W
<ul style="list-style-type: none"> • during no-load operation maximum 	2.5 W
Closed-loop control	
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	3 %
setting time	
<ul style="list-style-type: none"> • load step 10 to 90% typical 	5 ms
<ul style="list-style-type: none"> • load step 90 to 10% typical 	5 ms
<ul style="list-style-type: none"> • maximum 	5 ms
Protection and monitoring	
design of the overvoltage protection	< 60 V
response value current limitation typical	15 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Shutdown and periodic restart attempts
overcurrent overload capability in normal operation	overload capability 150 % I _{out} rated up to 5 s/min
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra low output voltage V_{out} according to EN 60950-1
operating resource protection class	Class I
leakage current	
<ul style="list-style-type: none"> • maximum 	3.5 mA
protection class IP	IP20
Approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking 	Yes
<ul style="list-style-type: none"> • UL approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 62368-1, UL 62368-1)
<ul style="list-style-type: none"> • CSA approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 62368-1, UL 62368-1)
<ul style="list-style-type: none"> • cCSAus, Class 1, Division 2 	No
<ul style="list-style-type: none"> • ATEX 	No

certificate of suitability	
<ul style="list-style-type: none"> • IECEx • NEC Class 2 • ULhazloc approval • FM registration 	<p>No</p> <p>No</p> <p>No</p> <p>No</p>
type of certification CB-certificate	Yes
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval • C-Tick • Regulatory Compliance Mark (RCM) 	<p>Yes</p> <p>No</p> <p>No</p>
certificate of suitability shipbuilding approval	No
shipbuilding approval	in process: DNV GL, ABS
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • DNV GL • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) 	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
EMC	
standard	
<ul style="list-style-type: none"> • for emitted interference • for mains harmonics limitation • for interference immunity 	<p>EN 55022 Class B</p> <p>EN 61000-3-2</p> <p>EN 61000-6-2</p>
environmental conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during transport • during storage 	<p>-30 ... +70 °C; with natural convection a monotonically increasing start-up from -25 °C, safe start-up from -40 °C</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p>
environmental category acc. to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection	Push-in terminals
<ul style="list-style-type: none"> • at input • at output • for auxiliary contacts 	<p>L1/+, L2/N/-, PE:PushIn for 0.5 ... 4 mm² single-core/finely stranded</p> <p>+1, +2, -1, -2, -3: PushIn for 0.5 ... 6 mm²</p> <p>13, 14 (alarm signal): 1 push-in terminal each for 0.2 ... 1.5 mm²</p>
width of the enclosure	70 mm
height of the enclosure	135 mm
depth of the enclosure	155 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	<p>45 mm</p> <p>45 mm</p> <p>0 mm</p> <p>0 mm</p>
net weight	1.5 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
electrical accessories	Redundancy module
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

