


Sales Region	Worldwide
Series	DRJ
Model	DRJ50
Status	 Production
Feature	Complies with SEMI F47
Options	European terminal
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	



Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	85 to 264Vac
Input Voltage Range[DC]	120 to 370Vdc
Efficiency	89.5% Typ.
Rated Output Voltage[DC]	24Vdc
Output Voltage Range[DC]	21.6 to 28.5Vdc
Maximum Output Current	2.1A
Maximum Output Power	50.4W

Package Type & Size

Package / Mounting	DIN rail
Industry Standard Size	
Width(W)	30mm Nom. (1.18in Nom.)
Height(H)	75mm Nom. (2.95in Nom.)
Depth(D)	90mm Nom. (3.54in Nom.)
Weight	180g Typ. (0.4lbs Typ.)

Other

Operating Temp. Range	-20 to 70°C
Cooling	Convection
Safety Standard(Certified)	CSA60950-1
	EN60950-1
	UL60950-1
	CSA62368-1
	EN62368-1
	UL62368-1
Safety Standard(Conformed)	CSA C22.2 No.107.1
	UL508
	Den-an Appendix 8 at 100VAC only

