


Sales Region	Worldwide
Series	DLP
Model	DLP75
Status	 Production (Not Recommended for New Design) Recommended Alternate Part No. : DRJ100-24-1 (Interchangeability is not guaranteed.)
Feature	
Options	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Compatible Bracket	
Accessories	Please refer to here.



Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	85 to 265Vac
Input Voltage Range[DC]	
Efficiency	83% Typ.
Rated Output Voltage[DC]	24Vdc
Output Voltage Range[DC]	21.6 to 28Vdc
Maximum Output Current	3.1A
Maximum Output Power	74.4W

Package Type & Size

Package / Mounting	DIN rail
Industry Standard Size	
Width(W)	50mm Nom. (1.97in Nom.)
Height(H)	97mm Nom. (3.82in Nom.)
Depth(D)	110mm Nom. (4.33in Nom.)
Weight	470g Typ. (1.0lbs Typ.)

Other

Operating Temp. Range	-10 to 60°C
Cooling	Convection

Safety Standard(Certified)	EN60529 IP20 CSA60950-1 EN60950-1 UL60950-1 CSA62368-1 EN62368-1 UL62368-1 CSA C22.2 No.14 UL508 EN50178 CATEGORY III (Primary)
Safety Standard(Conformed)	Den-an
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.