


■ Features

- AT-cut round shape crystal plate inside. Optimized for low harmonics
- Tight tolerance and stability. Ideal for communication equipment
- Available up to 200 MHz using 5th overtone crystal mode
- RoHS compliant versions are also available.



General Specifications

Item / Type	H49 ; 49T ; H49MJ ; 49TMJ series	
Frequency Range	H49	1.0 ~ 1.3MHz , 1.8 ~ 200.0MHz ( see Table 1 )
	49T	3.1 ~ 200.0MHz ( see Table 1 )
Load Capacitance	Series Resonance or Parallel ( 8 to 32 pF typical )	
Drive Level	100μ W ( 500μ W max. )	
Frequency Tolerance	AT-cut: ± 5 ppm , ± 10 ppm , ± 20 ppm or ± 30 ppm at 25°C	
	SL-cut: ± 50 ppm at 25°C	
Frequency Stability	See Table 2	
Aging	ΔF / F : ±2 ppm / year ( max. )	
Storage Temperature Range	- 50°C to 105°C	

Table 1

H49 ; 49T series resistance ( max. )

Freq.(MHz)	Hold Type	Osc. Mode	E.S.R.	Freq.(MHz)	Hold Type	Osc. Mode	E.S.R.
1.0 ~ 1.3	H49	SL , Fund.	5K Ω	7.1 ~ 10.0	H49 , 49T	AT , Fund.	35 Ω
1.8 ~ 3.0	H49	AT , Fund.	400 Ω	10.1 ~ 30.0	H49 , 49T	AT , Fund.	25 Ω
3.1 ~ 3.5	H49	AT , Fund.	150 Ω	30.1 ~ 45.0	H49 , 49T	AT , Fund.	20 Ω
3.5 ~ 5.0	H49 , 49T	AT , Fund.	100 Ω	24.0 ~ 100.0	H49 , 49T	AT , 3rd	40 Ω
5.1 ~ 7.0	H49 , 49T	AT , Fund.	50 Ω	80.0 ~ 160.0	H49 , 49T	AT , 5th	70 Ω

Table 2

Frequency stability Vs Operating temperature range

Temp. (°C) \ ppm	± 5	± 10	± 15	± 20	± 25	± 30	± 50	± 100 (SL-cut)
X -10 to 60°C	○	○	○	○	○	○	○	○
Y -20 to 70°C	▲	○	○	○	○	○	○	○
I -40 to 85°C	○	○	○	○	○	○	○	○

○ : available ; ▲ : contact Mercury

Outline Dimensions ( Unit : mm )

Dip type ( H49 , 49T )		Jacket type ( H49MJ , 49TMJ )																
	<table border="1"> <thead> <tr> <th></th> <th>H</th> </tr> </thead> <tbody> <tr> <td>H49</td> <td>13.6 ± 0.2</td> </tr> <tr> <td>49T</td> <td>11.2 ± 0.2</td> </tr> </tbody> </table>		H	H49	13.6 ± 0.2	49T	11.2 ± 0.2		<table border="1"> <thead> <tr> <th></th> <th>H</th> <th>W</th> </tr> </thead> <tbody> <tr> <td>H49MJ</td> <td>13.8 ± 0.2</td> <td>17.1 ± 0.2</td> </tr> <tr> <td>49TMJ</td> <td>11.4 ± 0.2</td> <td>14.7 ± 0.2</td> </tr> </tbody> </table>		H	W	H49MJ	13.8 ± 0.2	17.1 ± 0.2	49TMJ	11.4 ± 0.2	14.7 ± 0.2
	H																	
H49	13.6 ± 0.2																	
49T	11.2 ± 0.2																	
	H	W																
H49MJ	13.8 ± 0.2	17.1 ± 0.2																
49TMJ	11.4 ± 0.2	14.7 ± 0.2																