



Main

Range	PowerLogic
Product or component type	Remote display
Device application	Human-machine dialogue application
Range compatibility	PowerLogic PM8000
Display type	Colour TFT LCD

Complementary

Display resolution	320 x 240 pixels QVGA
Information displayed	Current Frequency Harmonic distortion Voltage System alarm Power Energy consumption I/O status
Messages display capacity	Graphic objects (bargraph, button, light...)
Local signalling	Alarm : red LED Status : green LED
Control type	5 x push-button
Connector type	RJ45
Provided equipment	3 m cable Mounting hardware
Mounting mode	Flush-mounted
Mounting support	Remote display on framework
Width	96 mm
Height	96 mm
Projecting depth	27 mm
Product weight	300 g

Environment

IP degree of protection	IP54 according to IEC 60529
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Product certifications	IEC

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1425 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.