

**DR706 provides a safe, reliable and comfortable phase rotation indication**

### Engineered with safety in mind

Unique bright LED display can be read in direct sunlight  
Ergonomically shaped to fit comfortably in the palm  
A range that can be adapted to your needs

### 100% safety and simplicity for the operator

All functions can be operated whilst wearing insulating gloves  
Indication by

**chasing green LEDs for clockwise rotation** and  
**chasing red LEDs for the counter-clockwise rotation**

One light = one function => better understanding

### Device designed for field use:

Heavy duty waterproof housing  
Can be used in all weathers  
Supplied in a soft case.  
Replaceable leads with European colour codes and L1/L2/L3 marking (other markings or colours to order).



### Spécifications:

Voltage range: 90V to 400 V AC  
AC frequency range : 50 Hz & 60 Hz  
Maximum rated voltage: 400 V three phase system.  
Category of use: 600V cat III or cat. IV  
Class: N = - 10 ° C to + 55 ° C  
Probes: Ø4 mm  
Protection : IP65(CATIV) IP54(CATIII)  
"Outside" type can be used in rain.

### Version :

Ref. : DR706xxxyp

xxx : III or IV (category)  
y : X for IP2X, N for no IP2X, F fused  
pp : country code ex: FR , DE, GB....

