
73 06 160 T KNIPEX X-Cut[®] Compact Diagonal Cutter







- Compact and 25 % less weight. Powerful and precise
- Cuts finest strands as well as multi-core cables and piano wires
- Box-joint design: highest stability with low weight
- · Doubly supported joint axis for heaviest duty
- High cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- 40% less force required compared with standard diagonal cutters of the same length
- Large opening width for thicker cables
- Cuts precisely, even through fine copper wires
- Compact, low-weight construction
- Universally usable, in the assembly, maintenance and production
- Chrome vanadium heavy-duty steel, forged, multi stage oil-hardened
- Pliers with integrated, insulated tether attachment point for a tool tether

40% less force required compared with standard diagonal cutters of the same length

with double mounted hinged joint

| Article No. | 73 06 160 T | | |
|--|---|----|-----------|
| | | | |
| EAN | 4003773081838 | | 1 Hallett |
| Pliers | chrome plated | 93 | |
| Head | | | |
| Handles | insulated with multi- component grips, VDE- tested with integrated insulated tether attachment point for a tool tether | | W |
| Insulation standard | IEC 60900 DIN EN 60900 | | |
| Cutting capacities medium hard wire (diameter) Ø mm | 3,8 | | |
| Cutting capacities hard wire (diameter) Ø mm | 2,7 | | |
| Cutting capacity copper cable, multiple- stranded (diameter) Ø mm | 12,0 | | |
| Cutting capacities piano wire (diameter) Ø mm | 2,2 | | |
| Cutting capacities soft wire (diameter) Ø mm | 4,8 | | |
| Length mm | 160 | | |
| Net weight g | 184 | | |
| | 1 | | |

technical change and errors excepted