

[NEOZED-Sicherungseinsatz], D01, 10 A, [gR], Un AC: 400 V, Un DC: 250 V, SILIZED



Model	
Product brand name	SENTRON
Product designation	NEOZED fuse link
Design of the product	SILIZED
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D01
Operating class of the fuse link	gR
Supply voltage	
Supply voltage	
• at DC	250 V
Operating voltage / rated value	400 V
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	6.9 W
Main circuit	
Operating current / rated value	10 A
Appearance	

Color coding of the fuse link	Red
Maximum short-circuit current breaking capacity (Icu) / at AC / rated value	50 kA

### Mechanical Design

Net weight	3 g
Ambient temperature	
• minimum	-5 °C
• maximum	40 °C

### Certificates

Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

### Declaration of Conformity

other

[Environmental Confirmations](#)



EG-Konf.

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5SE1310>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE1310>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5SE1310](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5SE1310)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>

