



PHOENIX CONTACT INC
MR K B BOEGLI, CHIEF STANDARDS ENG
PO BOX 4100
HARRISBURG PA 17111

RE: Project Number(s) - 02ME24013

Your most recent Certification is shown below. You may also view this information, or a portion of this information (depending on the product category), on UL's Online Certifications Directory at www.ul.com/database. Please review the text and contact the Conformity Assessment Services staff member who handled your project if revisions are required. For instructions on placing an order for this information in a 3 x 5-inch format, you may refer to the enclosed order form for UL Card Service.

XCFR2
Terminal Blocks - Component

January 27, 2003

PHOENIX CONTACT GMBH & CO KG
POSTFACH 1341, 32819 BLOMBERG GERMANY

E60425

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
BK4	28-12	CU	2	5-7	600	25	C	2(105)
BK4-FS	28-12	CU	2	5-7	150	20	C	2(105)
BK4-FS/FS	N/A	CU	1	N/A	150	20	C	2(105)
BK10	26-8	CU	2	11-15	600	50	C	2(105)
BK16	26-6	CU	2	11-15	600	65	C	2(105)
BK25/E	22-4	CU	2	18-25	600	85	C	2(105)
BK35/E	18-2	CU	2	30-50	600	115	C	2(105)
UK10-DREHSI(1)	6-24	CU	2	11-20	300	20	C	2(105)
ZFK10,ZFKI10	16-6	CU	2	—	600,600	60	B,C	2(105),4
ZFKN10	16-6	CU	2	—	600,600	55	B,C	2(105),4
ZFK10PE,ZFKI10PE	16-6	CU	2	—	—	60	B,C	2(105),4,6&
ZFK16,ZFKI16,ZFKN16	14-4	CU	2	—	600,600	65	B,C	2(105),4
ZFK16PE,ZFKI16PE	14-4	CU	2	—	—	65	B,C	2(105),4,6&
ZFK35	12-2	CU	2	—	600	120	C	2(105),4
ZFK35-PE	12-2	CU	2	—	—	—	C	2(105),4
(1) Followed by suffixes LA, LA/K, LED or LED/K, followed by 12, 24, 60 or 250, followed by (5x20), (5x25), (5x30) or (6.3x32), with or without suffixes -TE, -M.W.-K, -DM.								
UK10.3-HESI	8-24	CU	2	11-20	600	35	B,C	2(105)
UKH25,UHV25(1)	6-4	CU	2	40	600	85	B,C	2(105)
UKH50,UHV50,UKH50IB (1)	6-1/0	CU	2	70	600	150	B,C	2(105)
UKH95,UHV95(1)	2-4/0	CU	2	175	600	230	B,C	2(105)
UKH150	2-300	CU	2	270	600	285	B,C	2(105)
UHV150(1)	2-300	CU	2	270	600	285	B,C	2(105)
UKH240	2/0-500	CU	2	270	600	380	B,C	2(105)

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
UHV240(1)	500	CU	2	270	600	380	B,C	2(105)
AGK10-UKH	6-24	CU	2	11-20	600	65	B,C	2(105)
(1)Followed by suffixes -M8, -M10, -M12, -M16, -AS or KH, additionally followed by suffixed /M8, /M10, /M12, /M16, /AS, or /KH.								
FKDS,FKDSA(1)(4)	16-22	CU	2	N/A	300	10	B,D	2(105)
FKDSV,FKDSVA(1)(2)(4)	16-22	CU	2	N/A	300	10(6)	B,D	2(105)
FFKDS,FFKDSA(2)(4)(5)	16-22	CU	2	N/A	300	10(6)	B,D	2(105)
FFKDSA(2A)	16-22	CU	21	N/A	600	5(8)	B,D	2(105),#
FKDSP,	16-22	CU	2	N/A	300	10	B,D	2(105),#
FKDSPA1(4)(7)								
MFKDSP(2)(3)	18-22	CU	2	N/A	300	3.6	B,D	2(105),#
MFKDS-5.08(4)	16-22	CU	2	N/A	300	10	B,D	2(105)
MFKDSA-7.62(4)	16-22	CU	2	N/A	300	10	B,D	2(105)

(1)With or without suffix 1, followed by -5.08 or -7.62, may be followed by suffixes /SA and/or 5.08 or 10.16.

(2)With or without suffix 1, followed by suffix /H1, /H2, /V1 or /V2, followed by -5.08.

(2A)With or without 1, followed by /H1, /H2, /V1, /V2 followed by -7.62.

(3)Followed by /2, /3, /4, /6 or /7, followed by -5.80.

(4)Additional wire size of No. 12 AWG Sol.

(5)With or without 1, followed by /H or /V, followed by -2.54or -5.08.

(6)13.5 max., for factory-wiring.

(7)With or without suffix -MT, followed by -5.08 or -7.62.

(8) 10A max. 300V, 5A max. 600V, also 13A max. factory wiring at 150V.

FFKDS(5)	20-26	CU	2	N/A	150	6	B,D	2(105),4
FFKDS(6)	16-26	CU	2	N/A	300	6	B,C	2(105),4
FFKDSA(6)	16-26	CU	2	NA	300	6	B,C	2(105),4
FFKDSA(5)	20-26	CU	2	N/A	150	6	B,D	2(105),4
UK3-RETURN	12-30	CU	2	5-7	300	20	B,D	2(105)
UK5-RETURN	10-30	CU	2	5-7	300	30	B,D	2(105)
UK10-RETURN	6-24	CU	2	11-20	300	65	B,D	2(105)
UK3-RETURN-PE	12-30	CU	2	5-7	N/A	N/A	B,D	2(105),#
UK5-RETURN-PE	10-30	CU	2	5-7	N/A	N/A	B,D	2(105),#
UK10-RETURN-PE	6-24	CU	2	11-20	N/A	N/A	B,D	2(105),#
DFK4-Si(1)	30-10	CU	1	5-7	300	10	B,D	2(105),#

(1)Followed by 5 X 20/25, 5 X 30 or 6.3 X 32.

(5)With or without suffix 1, followed by /H, or /V and -2.54, or-5.08.

(6) With or without 1, followed by /H, or /V and -3.81, or -6.35.

SLKK5	10-26	CU	2	5-7	600	30	B,C	2(105),#
TT-SLKK5,	26-10	CU	2	5-7	600	30	B,C	2(105),#
TT-SLKK5-S,								
followed by suffixes	/26-12							
/12,/24,/48, /60,/								
110 followed								
by suffix AC or DC								

GSTB3/3-ST-7.62	30-10	CU	2	5-7	300	10	B,D	2(105),#
GSTB3/3-G-7.62	N/A	CU	1	N/A	300	10	B,D	2(105),#
STB3/3-ST-5.08	30-10	CU	2	5-7	300	10	B,D	2(105),#
STB3/4-ST-5.08	30-10	CU	2	5-7	300	10	B,D	2(105),#
STB3/3-G-5.08	N/A	CU	1	N/A	300	10	B,D	2(105),#
STB3/4-G-5.08	N/A	CU	1	N/A	300	10	B,D	2(105),#
DIK1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
DIKD1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
DIKD1.5-PV(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
DOK1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
DOK1.5(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
DOK1.5-2D(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
DOK1.5-TG	14-30	CU	2	5-7	300	15	B,D	2(105),#
DOKD1.5-TG	14-30	CU	2	5-7	300	15	B,D	2(105),#

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
DLK2.5-PE	14-30	CU	2	5-7	300	15	B,D	2(105),#
DLK4-PE	10-30	CU	2	5-7	600	30	B,D	2(105),#
DLKB2.5-PE	14-30	CU	2	5-7	300	15	B,D	2(105),#
(1)May be followed by suffixes -LA, -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -220, -24GN, -60GN, -220GN, with or without suffixes /O-M, /U-O, /O-MO, /MU-O.								
VIOK1.5(2)(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
VIOK1.5-2D(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
VIOK1.5-3D-PE(1)	14-30	CU	2	5-7	300	15	B,D	2(105),#
(1)May be followed by suffixes -LA, -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -220, -24GN, -60GN, -220GN, with or without suffixes /O-M, /U-O, /O-MO, /MU-O.								
GKDS,GKDS/E,LOE	30-14	CU	1	5-7	250	15	B,C,D	2(105),#
KDS	30-14	CU	2	5-7	250	15	B,C,D	2(105),#
KDS2.5(1)	30-12	CU	1	5-7	300	15	B,C,D	2(105),#
KDS3(2)	28-12	CU	2	5-7	300	15	B,C,D	2(105),#
KDS3(3)	28-12	CU	2	5-7	300	15	B,D	2(105),#
(1)Followed by suffixes -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -LA/EK.								
(2)Followed by suffixes -MT, -PMT or -Si.								
(3)Followed by suffixes -SILED12, -SILED24, -SILED60, -SILED250.								
GMKDS(1)	30-14	CU	2	5.0	300	10	B	2(105)
GSMKDS(1)	30-14	CU	2	5.0	300	10	B	2(105)
(1)Followed by /1 or 2 digit number, with or without -7.62.								
HC-KA(1)	22-12	CU	2	5.0	300	15	B,C	2(105)
(1)Followed by suffix number 6, 10, 16 or 24.								
MBK4(1)	26-10	CU	2	5-7	600	30	B,C	2(130)
(1)With or without suffixes -PE, -2PE, -TK/2 or -TK/3.								
MSLKG2.5	28-12	CU	2	5-7	300	10	B,C	2(105),#
MSLKG4	28-12	CU	2	5-7	N/A	N/A	B,C	2(105),#
MSLKG5	26-10	CU	2	5-7	N/A	N/A	B,C	2(105),#
MTK(1)	28-12	CU	2	5-7	300	10	B,D	2(105),#
MTKD(2)	28-12	CU	2	5-7	300	10	B,D	2(105),#
(1)With or without suffixes -Loe/Loe, -Loel, -Loel/PR, -P/P, -D or -D-P/P.								
(2)Followed by Suffix -CU/CUNI, -FE/CUNI, -NICR/CUNI, -NICR/NI, -NICRSI/NISI, -E-CU/A-CU or -S-CU/E-CU.								
OTTA2.5	N/A	CU	1	11	600	20	B,C	2(105),#
OTTA2.5-P/P	N/A	CU	1	11	600	20	B,C	2(105),#
OTTA6	N/A	CU	1	20	600	30	B,C	2(105),#
OTTA66-P/P	N/A	CU	1	20	600	30	B,C	2(130),#
OTTA6-T	N/A	CU	1	20	600	30	B,C	2(105),#
OTTA6-T-P/P	N/A	CU	1	20	600	30	B,C	2(105),#
OTTA25-M5	N/A	CU	1	40	600	115	B,C	2(105),#
OTTA250M6	N/A	CU	1	40	600	115	B,C	2(105),#
OTTA2.5-PE	N/A	CU	1	11	600	20	B,C	2(105),#
OTTA6-PE	N/A	CU	1	20	600	30	B,C	2(105),#
UDKE3-PE	12-30	CU	2	5-7	N/A	N/A	B,C	2(105),#
UDK4-PE	10-30	CU	2	5-7	N/A	N/A	B,C	2(105),#
USK4-FS/FS(1)	N/A	CU	1	N/A	600	20	B,C	2(105),#
(1)Followed by suffixes (6-2.8-0.8), (8-2.8-0.8), (4-2.8-0.8/2VR-2.8) or (4-2.8-0.8/3-2.8).								
U3K2.5(1)	30-12	CU	2	5-7	600	20	B,C	2(105),#
(1)With or without suffixes -LA12, -LA24, -LA48, -LA60 followed by RD or RT and /OM, or -LA220.								
USiGST-Si(1)	8-18	CU	2	20	600	40	C	2(105),#
USiGST1-Si(1)	8-18	CU	2	20	600	40	C	2(105),#
(1) With suffixes ST-Si, or ST1-Si, with or without suffixes SILED 12, SILED 24, SILED 60, SILA 250, or SILA 5000.								
PIK4(2)	28-12	CU	2	5-7	300	20	B,C	2(105),#
PIK4-PE(2)	28-12	CU	2	5-7	300	20	B,C	2(105),#
PIK6 (1)	26-8	CU	2	5-7	300	50	B,C	2(105), #
PIK6-PE (1)	26-8	CU	2	5-7	300	50	B,C	2(105), #
UK-SI	28-12	CU	2	5-7	300	10	B,C	2(105), #

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
Note: (1) With Suffixes -L/L, -L/N, or -L/NT.								
Note: (2) With Suffixes -L or /L, with or without Suffixes /L, /N, /NT, /NTB.								
Note: (3) 25A max. factory-wiring only.								
GESK(1)	22-12	CU	2	5.0	600	7	B,C	2(105)
(1)With or without suffixes -K, -K2, -ST, -ST2, may be followed by -F1 or -F2.								
DKBD(1)	30-14	CU	2	5-7	300	10	B,D	2(105)
(1)Followed by /one or two digit number, by suffix -MT or MT2L, with or without suffix -5.08.								
TRKS10(1)	6-24	CU	1	11-20	300	65	B,C	2(105),#
TRKSD10(1)	6-24	CU	1	11-20	600	65	B,D	2(105),#
TRKSD10/3(1)	6-24	CU	1	11-20	600	65	B,D	2(105),#
(1)With suffix Gray or Orange.								
UK5-HESi(1)	26-10	CU	2	5-7	600	12	C	2(105)
(1)With suffix -LED followed by 12, 24or 60, or -LA followed by 250 or 500.								
UKK3MSTBVH5.08.	30-12	CU	2	5-7	300	10	B,C,D	2(105),#
UKK4-FS	10-30	CU	2	5-7	300	20	B,C	2(105),#
VBST4-FS(6-2.0-8)ST4	10-30	CU	2	5-7	300	20	B,C	2(105),#
UKK4-FS/FS	N/A	CU	1	N/A	300	20	B,C	2(105),#
UVKB4-FS	28-12	CU	2	5-7	300	12	C	2(105),#
UVKB4-FS/FS	N/A	CU	1	N/A	300	25	C	2(105),#
UK3MSTBV5.08(1)	26-12	CU	2	5.0	300	20	B,D	2(105),#
(1)With or without suffixes -LA12, -LA24, -LA48, -LA60 followed by -RD or -RT.								
UK6.3-HESi(1)	26-8	CU	2	11-15	600	25	B,C	2(105),#
(1)With or without suffixes -LED followed by 12, 24or 60, or suffix -LA followed by 250 or 500.								
VIOK1.5(2)(1)	14-30	CU	—	5-7	300	15	B,D	2(105),#
VIOK1.5-2D(1)	14-30	CU	—	5-7	300	15	B,D	2(105),#
VIOK1.5-3D-PE(1)	14-30	CU	—	5-7	300	15	B,D	2(105),#
USEN14	2-20	CU	—	35-40	600	16	B,C	2(105),4
USEN18	2-20	CU	—	35-40	600	63	B,C	2(105),4

(1)May be followed by suffixes -LA, -LA12, -LA24, -LA48, -LA60, followed by RD or RT, -220, -24GN, -60GN, -220GN, with or without suffixes /O-M, /U-O, /O-MO, /MU-O.

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
MBK3/E-Z	28-12	CU	2	5-7	600	20	B,C	2(105)
MBK3/E-ZBU	28-12	CU	2	5-7	600	20	B,C	2(105)
MBK6/E	8-26	CU	2	11-15	600	50	B,C	2(105)
MBK5/E-Z,BU	26-10	CU	2	5-7	600	30	B,C	2(105),4
MBK5/E-Z-PE	26-14	CU	2	5-7	—	—	B,C	2(105),4
MSLKG6	8-26	CU	2	11-15	N/A	N/A	B,C	2(105),*
UK1.5N	30-14	CU	2	4	300	15	B,C	2(105)
UK2.5N	12-30	CU	2	5-7	300	20	B,C	2(105)
UK2.5	14-30	CU	2	5-7	300	15	B,C	2(105)
UK3	12-28	CU	2	5-7	600	20	B,C	2(105)
UK4	12-28(#)	CU	2	5-7	600	20	B,C	2(105)
UK5	10-26(#)	CU	2	5-7	600	30	B,C	2(105)
UK10	8-26	CU	2	11-15	600	50	B,C	2(105)
UK16	6-24	CU	2	11-15	600	65	B,C	2(105)
UK3N	12-28	CU	2	5-7	600	20	B,C	2(105)
UK5N	10-30(#)(##)	CU	2	5-7	600	30	B,C	2(105)
UK6N	8-26(1)	CU	2	15	600	50	B,C	2(105)
UK6-FSI/C,-LED12, -LED24	26-8	CU	2	15	300	30	B,C	2(105),4*
UK10N	6-24	CU	2	11-20	600	65	B,C	2(105)
UK16N	4-22	CU	2	18-25	600	85	B,C	2(105)
UIK16	4-22	CU	2	18-25	600	85	B,C	2(105),4
UIK35	2-18	CU	2	30-50	600	115(+)	B,C	2(105),4
UK25	4-22	CU	2	18-25	600	85	B,C	2(105),4
UK35	1/0-18	CU	2	30-50	1000	150	B,C	2(105)

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
UK35-PE/N	1/0-18	CU	2	30-50	600	150	B,C	2(105),*

(#) Additional wire combination rating of two No. 14AWG Cu stranded wires.

(##) Additional multiple wire rating of three No. 18 AWG Cu. stranded for field and factory-wiring.

(+) 130A max for factory-wiring only.

(1) Additional multiple wiring combination rating of two No. 12 AWG Cu. str. to 2 No. 18 AWG Cu. str. for field and factory-wiring, same size wires only.

UHSK/S2000	26-8	CU	2	11-15	1000	50	—	2(105),4
UKK5(2)	10-26	CU	2	5-7	600	30	B,C	2(105)
UKK5-PV	26-10	Cu	2	5-7	300	15	B,C	2(105),4,*
UKKB5	10-26	CU	2	5-7	600	30	B,C	2(105)
UKK5-HESI(5x20)	26-10	CU	2	5-7	600	15(3)	B,C	2(105),4
UKK5-HESI(6.3x32)	26-10	CU	2	5-7	600	15(3)	B,C	2(105),4
UKK5-DIO/O-U	10-26	CU	2	5-7	600	30	B,C	2(105),#
UKK5-DIO/U-O	26-10	CU	2	5-7	600	10	B,C	2(105),#
UKK5-DIO/UL-UR	26-10	CU	2	5-7	600	10	B,C	2(105),#
UKK5-2DIO/O-UL/ UR-UL	26-10	CU	2	5-7	600	15	B,C	2(105),#
UKK3	12-28	CU	2	5-7	600	20	B,C	2(105)
UKKB3	12-28	CU	2	5-7	600	20	B,C	2(105)
UKKB3-TP(2.4X0.8)L	24-20/ 28-12	CU	2/1	5-7	300	5	B,D	2(105),4,#
UKKB3-TP(2.4X0.8)Q	24-20/ 28-12	CU	2/1	5-7	300	5	B	2(105),4,#
UKKB10	6-24	CU	2	20	600	65	B,C	2(105)
UKKB10-2.5	6-24(1)	CU	2	20	600	65	B,C	2(105)
UKKB10-2.5PV	6-24(1)	CU	2	20	600	65	B,C	2(105)

(1) Top level terminals are rated No. 12-30 AWG cu sol/str (field/factory-wiring), 20A, 600v, 7 lb.-in. torque.

(2) May be followed by suffixes -LA60RD/U-O, or LA230.

(3) Lower level terminals rated 30A max; fused upper level rated 15A max.

USK4	12-28	CU	2	5-7	600	20	B,C	2(105)
USK10	8-26	CU	2	11-15	600	50	B,C	2(105)
USK16	6-24	CU	2	11-15	600	65	B,C	2(105)
USST6	14 max.	Cu	1	11-15	600	15	B,C	2(105),#
TT-UK5 w/suffixes/ 12,/24,/48,/60 and by AC or DC	26-10	CU	2	5-7	12-110	30	B,C	2(105), 4,*
URK-ND, -ND2	24-6	CU	2	11-15	600	65	B,C	2(105),4
SDKK6(4)	24-8	CU	2	15	600	26	B,C	2(105),#
GMKDS3/2(2)	12-30	CU	2	5-7	300	15	B,D	2(105)
GMKDS3/3(2)	12-30	CU	2	5-7	300	15	B,D	2(105)
GMKSP3/2(2)	12-30	CU	2	5-7	300	15	B,C	2(105)
GMKDS3/3(2)	12-30	CU	2	5-7	300	15	B,C	2(105)
GSMKDS3/2(2)	12-30	CU	2	5-7	300	15	B,D	2(105)
GSMKDS3/3(2)	12-30	CU	2	5-7	300	15	B,D	2(105)

(2) May be followed by -7.62.

(4) Followed by one or two digit number, with or without suffixes OBEN, UNTEN and/or NZ.

MKDSF3/2(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/3(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/4(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/8(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/12(1)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKDSF3/2-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKDSF3/3-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKDSF3/4-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)

(1) May be followed by -5.08.

MKDSF3/8-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKDSF3/12-S01(1)	12-30	CU	2	5-7	300	10	B,D	2(105)

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
MKDSFW3/2	12-30	CU	2	5	300	15	B,D	2(105)
MKDSFW3/3	12-30	CU	2	5	300	15	B,D	2(105)
MKDSP3/2(1)	12-30	CU	2	5	300	15	B,D	2(105)
MKDSP3/3(1)	12-30	CU	2	5	300	15	B,D	2(105)
SMKDS1.5/2(3)	12-30	CU	2	5-7	300	10	B,D	2(105)
SMKDS1.5/3(3)	12-30	CU	2	5	300	10	B,D	2(105)
SMDKS2.5/2###	30-12	CU	2	5-7	300	10	B,D	2(105)
SMKDS2.5/3###	30-12	CU	2	5-7	300	10	B,D	2(105)

(1) May be followed by -5.08.

(3) May be followed by -5.08, -6.35 or -9.5.

SMKDS3/2(3)	12-30	CU	2	5-7	300	15	B,D	2(105)
SMKDS3/3(3)	12-30	CU	2	5-7	300	15	B,D	2(105)
SMKDS5/2(3)	10-30	CU	2	5-7	300	30	B,C	2(105)
SMKDS5/3(3)	10-30	CU	2	5-7	300	30	B,C	2(105)
SMKDSP1.5(3)	14-30	CU	2	5.0	300	15	B,C	2(105)
SMKDSFU2.5/X-5.08	12-30	CU	2	5-7	300	10	B,D	2(105)
UK5-MTK-P/P	22-12	CU	2	5	600	15	B,C	2(105)*
DFLK-D(1) Sub/B	12-30	CU	2	5-7	125	2.5	B	2(105)
DFLK-D(1) Sub/S	12-30	CU	2	5-7	125	2.5	B	2(105)

(1) Followed by one or two-digit number.

(3) May be followed by -5.08, -6.35 or -9.5.

UDK4-MTK	30-10	CU	2	5-7	600	15	B,C	2(105)*
UDK4-MTK-P/P	30-10	CU	2	5-7	600	15	B,C	2(105)*
UKK5-MTK-P/P	26-12	CU	2	5-7	300	15	B,C	2(105)*
UKK5-MTK-P/ P-LA,-MTKD(++)	26-12	CU	2	5-7	300	15	B,C	2(105)*
UKK5-T	26-12	CU	2	5-7	300	15/25	B,C	2(105)*
UKK5-TG	26-12	CU	2	5-7	300	15/25	B,C	2(105)*
URELG(1)PMTK, -RD	30-12	CU	2	5-7	300	10	B,C	2(105)*
TT-UKK5-TBE	26-12	CU	2	5-7	300	15	B,C	2(105)*

(1) Followed by 2, 3, 4, or 7.

(++) May be followed by 24, 48 or 60, may be followed by RT/O-U.

UDMTK5-P/P	26-12	CU	2	5-7	300	15	B,C	2(105)*
UDMTKB5-P/P	26-12	CU	2	5-7	300	15	B,C	2(105)*
UDMTK5-TWIN-P/ P	26-12	CU	2	5-7	300	8	B,C	2(105)*
UDK-RELG	30-12	CU	2	5-7	300	20	B,C	2(105),4*
UDK4-TG	30-12	CU	2	5-7	300	15	B,C	2(105),4#
DFK4-PE	30-10	CU	2	5-7	N/A	N/A	B,D	2(105),4*
DFK4	10-30	CU	2	5-7	300	15	B,D	2(105),4*
DFK/DB4	10-30	CU	2	5-7	300	15	B,D	2(105),4*
DFK-WW(1x1)	28-12	CU	2	5-7	300	10	B,D	2(105),4*
DFK-TP(1.6x0.8)	28-12	CU	2	5-7	300	10	B,D	2(105),4*
DFK-TP(2.4x0.8)	28-12	CU	2	5-7	300	10	B,D	2(105),4*
DFK-2.8	28-12	CU	2	5-7	300	15	B,D	2(105),4*
DFK/DP-2.8	28-12	CU	2	5-7	300	15	B,D	2(105),4*
DFK-2.8 FRONT 2.5	28-12	CU	2	5-7	300	15	B,D	2(105),4*
DFK/DP-2.8 FRONT 2.5	28-12	CU	2	5-7	300	15	B,D	2(105),4*
TRK1.5,-N,-S,-S01, TRK1.5-S02,-FS, TRK1.5-Blau So1	22-14	CU	2	7	300	15	B,C	2(105)*
TRK2.5,TRK2.5-FS	22-12	CU	2	7	600	20	B,C	2(105)*
TRK2.5N,-GY,-FS-GY, TRK2.5N-OG,-FS-OG, TRK2.5BU SO1	22-12	CU	2	7	600	20	B,C	2(105)*

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
TRK4,-FS,-Blau Sol1	16-10	CU	2	11	600	30	B,C	2(105)*
TRKS4,TRKS4-FS	30-10	CU	2	5-7	600	30	B,C	2(105)*
TRKS4-Si	30-10	CU	2	5-7	600	8	B,C	2(105)*
TRKS4-Si/K	30-10	CU	2	5-7	600	8	B,C	2(105)#
TRK1.5/2(1)	22-14	CU	2	7	300	15	B,C	2(105)*
TRK1.5/3(1)	22-14	CU	2	7	300	15	B,C	2(105)*
(1) With or without suffixes -N, -FS, -N-FS followed by OG.								
TRKS4/1-Si(6.3x32), (5x30)	30-10	CU	2	5-7	600	10	B,C	2(105)#
TRKS4/3GY,OR	30-10	CU	2	5-7	600	30	B,C	2(105)#
TRK10	10-6	CU	2	11	600	55	B,C	2(105)#
TRK10 Blau Sol	10-6	CU	2	11	600	55	B,C	2(105)#
VTRK(Z)4, -GY, -OG	30-10	CU	2	5-7	300	30	B,C	2(105)#
VTRK(Z)4-SI/C,-GY, -OG	30-10	CU	2	5-7	300	10	B,C	2(105)#
TRK2.5-Si	22-12	CU	2	7	300	8	B,C	2(105)#
TRKSD4,-FS	30-10	CU	2	5-7	600	30	B,C	2(105)#
ZRTK4	24-12	CU	2	N/A	600	20	B,C	2(105)*
USLKG2.5, -1	30-12	CU	2	5-7	N/A	N/A	B,C	2(105),4#
USLKG1.5N	30-14	CU	2	5-7	N/A	N/A	B,C	2(105),4#
USLKG2.5N	30-12	CU	2	5-7	N/A	N/A	B,C	2(105),4#
USLKG3, -1	28-12	CU	2	5-7	N/A	N/A	B,C	2(105),4#
USLKG4, -1	26-12	CU	2	5-7	N/A	N/A	B,C	2(105),4#
USLKG5, -1,	26-10	CU	2	5-7	N/A	N/A	B,C	2(105),4#
USLKG6N	26-8	CU	2	11-15	N/A	N/A	B,C	2(105),4#
USLKG10, -1	26-8	CU	2	11-15	N/A	N/A	B,C	2(105),4#
USLKG10N, -1	24-6	CU	2	11-20	N/A	N/A	B,C	2(105),4#
USLKG16, -1	24-6	CU	2	11-15	N/A	N/A	B,C	2(105),4#
USLKG35, -1	18-1/0	CU	2	30-50	N/A	N/A	B,C	2(105),4#
USLKG50,	1/0-6	CU	2	70	N/A	N/A	B,C	2(105),4#
USLKG50IB								
USLKG95	2-4/0	CU	2	200	N/A	N/A	B,C	2(105),4#
UISLKG16	22-4	CU	2	18-25	N/A	N/A	B,C	2(105),4#
USLKG16N, -1	22-4	CU	2	18-25	N/A	N/A	B,C	2(105),4#
UKK5-PE	26-10	CU	2	5-7	N/A	N/A	B,C	2(105),4#
UKK85-PE	26-10	CU	2	5-7	N/A	N/A	B,C	2(105),4#
UK10-PE/N	26-8	CU	2	11-15	N/A	N/A	B,C	2(105),4#
UK16-PE/N	24-6	CU	2	11-15	N/A	N/A	B,C	2(105),4#
FAA40,FAA40/20	12-28	CU	2	5-7	300	10	B,	2(105),A
MC1.5/X-ST(1), -ST1(1)	14-30	CU	2	2-4	300	8	B,D	2(105)*
MC1.5/X-STF(1), -STF1(1)	14-30	CU	2	2-4	300	8	B,D	2(105)*
MCVR1.5/X-ST, -STF(1)	14-30	CU	2	4	300	8	B,D	2(105)*
MCVR1.5/X-STFL(1)	14-30	CU	2	4	300	8	B,D	2(105)*
MCVR1.5/X-STFR(1)	14-30	CU	2	4	300	8	B,D	2(105)*
MCVW1.5/X-ST(1)	14-30	CU	2	4	300	8	B,D	2(105)*
MCVW1.5/X-STF(1)	14-30	CU	2	4	300	8	B,D	2(105)*
MCVW1.5/X-STFL(1)	14-30	CU	2	4	300	8	B,D	2(105)*
MCVW1.5/X-STFR(1)	14-30	CU	2	4	300	8	B,D	2(105)*
IMC1.5/X-ST(1)	14-30	CU	2	4	300	8	B,D	2(105)*
IMC1.5/X-SRF(1)	14-30	CU	2	4	300	8	B,D	2(105)*
(1) Followed by suffix -3.5, -3.81 or -5.08.								
FRONT-MC1.5/X-ST(1)	16-30	CU	2	4	300	8	B,D	2(105)*

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
FRONT-MC1.5/ X-STF(1)	16-30	CU	2	4	300	8	B,D	2(105)*
MCV1.5/ X-G-3.81-SMD	—	CU	1	—	300	8	B,D	2(105)*
MCV1.5/X(2)(1), -THT	—	CU	1	—	300	8	B,D	2(105)*
DFX1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)*
MCDVU1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)*
SMC1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)*
MC1.5/X(2)(1), -THT	—	CU	1	—	300	8	B,D	2(105)*
MCD1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)*
MCDV1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)*
IMC1.5/X-G-3.81	—	CU	1	—	300	8	B,D	2(105)*
IMCV1.5/X-G-3.81	—	CU	1	—	300	8	B,D	2(105)*
MCO1.5/ X-GL,-GR-3.81	—	CU	1	—	300	8	B,D	2(105)*
MCVU1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)*
MCVK1.5/X(2)(1)	—	CU	1	—	300	8	B,D	2(105)*
EMC1.5/X-G, -GF-3.5	—	CU	1	—	300	8	B,D	2 (105),*
EMC1.5/X-G, -GF-3.81	—	CU	1	—	300	8	B,D	2 (105),*
EMCV1.5-G, -GF-3.5	—	CU	1	—	300	8	B,D	2 (105),*
EMCV1.5-G, -GF-3.81	—	CU	1	—	300	8	B,D	2 (105),*
MCC1/X-ST-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)
MCC1/X-STF-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)
MCC1/X-STZ-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)
MCC1/X-STZF-3.81	(3)	CU	1	N/A	300	(4)	B,D	2 (105)

(1) Followed by suffix -3.5, -3.81 or -5.08.

(2) Followed by suffix -G, -G1, -GF, -G1F, -GFD, or -G0.

(3) No. 24-22 AWG Cu, stranded with MCC-MT0.25-0.5 crimp contact; No. 20-18 AWG Cu. stranded with MCC-MT0/5-1 crimp contact.

(4) 5A max. with MCC-MT0.25-0.5 crimp contact; 8A max. with MCC-MT0.5-1 crimp contact.

PSC1.5(/3 or /5)-F	16-30	CU	2	4	300	8	B,D	2(105)*
PSC1.5(/3 or / 5)-M,-PE	14-30	CU	1	—	300	8	B,D	2(105)*
FK-MCP1.5/X-ST or -STF(1)	16-28	CU	2	—	300	8	B,D	2(105)*
MCVU1.5/X-GFD	14-30	CU	2	4	300	8	B,D	2(105)*
MCVK1.5/X-GFD	14-30	CU	2	4	300	8	B,D	2(105)*
DFK5-9.5#(3)	30-10	CU	2	5-7	600	30	B,C	2(105)*
DMKDS2.5	30-14	CU	2	5-7	300	10	B,D	2(105)*
DMKDS-FS, -FSI	—	CU	1	—	300	10	B,D	2(105)*

(1) Followed by suffix -3.5, -3.81 or -5.08.

FL#(4)	—	—	1	—	300	10	B,D	2(105),*
KDS4#(3)(10)	30-10	CU	2	5-7	300	30	B,D	2(105),*
KDSP1.5/X(3)	30-14	CU	2	5-7	300	15	B,D	2(105),*
KDSP4/X(3)(10)	30-10	CU	2	5-7	300	30	B,D	2(105),*
MKDS1#(3)	30-16	CU	2	2.5	300	10	B,D	2(105),*
MKDS1.5/X#(3)	30-14	CU	2	5	300	15	B,D	2(105),*
MK3DS1/X-3.81 (14)	30-16	CU	2.5	4	300	10	B,D	2(105),*
MKDS3/X	30-12	CU	2	5-7	300	15	B,D	2(105),*
MKDSA3/X#(3)	30-12	CU	2	5-7	300	#(6)	B,D	2(105),*
MKDS3/ X-B5.08,-BK,-BU,-GNYE	30-12	CU	2	5-7	300	#(6)	B,D	2(105),*
MKDS5/X#(3)	30-10	CU	2	5-7	600	30	B,C	2(105),*
MKDS5 (8A)(10)	30-10	CU	2	5-7	300	30	B,C	2(105),4,#

Cat. No.	Wire Range	Wire Type	FW	TQ b In.	V	A	UG	CA
MKDS5HV (8A)	30-10	CU	2	5-7	600/300 (10)	30	B,C	2(105),4,#
MKDSV5HV (8A)	30-10	CU	2	5-7	300	30	B,C	2(105),4,#
MKDS5 (9A)	30-10	CU	2	5-7	600	30	B,C	2(105),4,#
MKDSV5 (9A)	30-10	CU	2	5-7	600	30	B,C	2(105),4,#
MKDS5HV (9A)	30-10	CU	2	5-7	600	30	B,C	2(105),4,#
MKDSV5HV (9A)	30-10	CU	2	5-7	600	30	B,C	2(105),4,#
MKDSO5/3(4)	30-10	CU	2	5-7	300	30	B,C	2(105),*
MKDSO2.5/X-L,-R	30-12	CU	2	5-7	300	10	B,C	2(105),*
SMKDSNF1.5X(5)(6)	30-14	CU	2	4.5	300	10	B,C	2(105),*
MKDS5/2-7.62, MKDS5/3-7.62, MKDS5/2-7.62 BeigeS01, MKDS5/3-7.62 BeigeS01	30-10	CU	2	5-7	300	30	B,D	2(105),*
MKDSN1.5(6), MKDSNB1.5#(3)	30-14	CU	2	4.5	300	10	B,D	2(105),*
MKDSN2.5(3)	30-12	CU	2	5-7	300	10	B,D	2(105),#
MKDS1.5/2,/3N-5.08	30-14	CU	5	5-7	300	10	B,D	2(105),#
MKDSFW1.5(3)#	30-12	CU	2	2.5	300	10	B,D	2(105),#
MK3DSN1.5/X#(6) (14)	30-14	CU	2	4.5	300	10	B,D	2(105),*
MK3DSNMH/X#	30-14	CU	2	4.5	300	10	B,D	2(105),*
GMKDSN1.5/X##	30-14	CU	2	4.5	300	10	B,D	2(105),*

(3) Followed by /one or two digit number.

(4) Followed by -L or -R and 6.35, with or without -BK.

(5) Followed by 5.08, with or without BK.

(6) Also covered for multiple wire combination of two No. 18 AWG Cu. str. for field or factory-wiring.

(14) Multiple wire combination of three No. 26, 24, or No. 22 AWG Cu stranded wires for field and factory-wiring.

(#) May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, BEIGE S01.

(8A) Followed by Suffixes /2 or /3 and -9.5 or -9.52.

(9A) Followed by Suffixes /2 or /3 and -9.5 or -9.52 and by Suffix Z.

(10) 600 V rating at max rated ampacity based on omitting terminals from alternating poles or by providing barriers of suitable insulating materials between poles of opposite polarity.

(10) Field-wiring pressure screw terminals comply with 600V spacings and dielectric test requirements.

GSMKDSN1.5/X##	30-14	CU	2	4.5	300	10	B,D	2(105),*
MKKDS1#(3)	30-16	CU	2	2.5	300	10	B,D	2(105),*
SMKDS1#(3) (7)	30-16	CU	2	2.5	300	10	B,D	2(105),*
SMKDS1.5(/2, / 3)-3.05, SMKDSV1.5(/2, / 3)-3.05	30-16	CU	2	2.5	300	10	B,D	2(105),4*
MKDSP1.5#(3)	30-14	CU	2	5	300	10	B,D	2(105),*
MKDSP2.5#(3)	30-12	CU	2	5-7	300	10	B,D	2(105),*
MKDSP10/2-10.16	20-6	CU	2	15	600	57	B,C	2(105),*
MKDSP10/3-10.16	20-6	CU	2	15	600	57	B,C	2(105),*
MKDSP10HV/1 or / 2-digit number, -10.16	20-6	CU	2	15	600	57	B,D	2(105),4,*
MKDSP10HV/1 or / 2-digit number, -12.7	20-6	CU	2	15	600	57	B,D	2(105),4,*
EMKDSP2.5#(3)	30-12	CU	2	5-7	300	10	B,D	2(105),*
EMKDS1.5(3)#	30-14	CU	2	2.5	300	10	B,D	2(105),#
MKDS1.5/X(3)#	30-14	CU	2	2.5	300	10	B,D	2(105),#
MKSD2.5#(3)	30-12	CU	2	5-7	300	20	B,D	2(105),*
MKDSFW1.5/X#(3)	30-14	CU	2	5	300	10	B,D	2(105),*
MKDSW3/X#(3)	30-12	CU	2	5-7	300	#(6)	B,D	2(105),*
MKKDS5/X#(3)(10)	30-10	CU	2	5-7	600	30	B,C	2(105),*

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
MKKDSN1.5#(3)(6)	30-14	CU	2	4.5	300	10	B,D	2(105),*
MKKDSN1.5/ X(3)HIL	30-14	CU	2	4.5	300	10	B,D	2(105)
MKKDSNH1.5(3)(4)(6)	30-14	CU	2	4.5	300	10	B,D	2(105),*
MK3DSNMH1.5#(3)(6)	30-14	CU	2	4.5	300	10	B,D	2(105),*
MKDSP25X-15.00, -F	20-10,	CU	2	22,	600	125	B,C	2(105),4
-FL, -FR	8-2			40				

(3) Followed by /one or two digit number.

(#) May be followed by suffixes -3.5, -3.81, -5.08, -6.35, -7.62, Beige S01.

(6) Also covered for multiple wire combination of two No. 18 AWG Cu. str. for field or factory-wiring.

(7) May be followed by suffix BK, HT, VO.

SMKDSN1.5#(3)(6)	30-14	CU	2	4.5	300	10	B,D	2(105),*
UEGM22.5,25,40/ 1,40/2	30-12	CU	2	5-7	300	10	B,D	2(105),*
UEGH(8)	30-12	CU	2	5-7	300	10	B,D	2(105),*
MPT0.5/X#-2.54	30-20	CU	2	1.0	125	6	B	2(105),*
VDFK4(7)	30-10	CU	2	5-7	300	30	B,D	2(105),*
VDFK6(7)	8-26	CU	2	15	300(10)	50	B,D	2(105),*
HK4-FS,-FS/FS#(1)	12-28	CU	2	—	250	25	B,C	2(130),*
K4/E, SSK/ N0525,UK4#(2)	12-28	CU	2	—	250	25	B,C	2(130),*

"X" in Cat. No. denotes 1 or 2 digit number.

++ May be followed by suffixes 24, 48 or 60, and/or RT/O-U.

(7) With or without suffix /K and/or -DP, -GYNE, or WH.

(8) Followed by suffixes 22.5, 25, 27.5, 40, 42.5, or 45 with or without /1, or /2, and/or SMD.

PC4/X(-1)-7.62	30-10	Cu	2	5-7	600	30	B,C	2(105),D*
PC4HV/X-ST-7.62	30-10	Cu	2	5-7	600	30	B,C	2(105),4*
PCVK4-7.62(3)	30-10	Cu	2	5-7	600	30	B,C	2(105),4*
UPCV3K4-G-7.62	30-10	Cu	2	5-7	300	30	B,C	2(105),4*
PC4/X(-1)-15.24-1	30-10	Cu	2	5-7	600	30	B,C	2(105),4*
PC4/X(-1)-15.24-2	30-10	Cu	2	5-7	600	30	B,C	2(105),4*
PCC4/X-ST-7.62(A)	20-18, 16-14	Cu	1	—	600	10	B,C	2(105),4*
PC4/X(-G, -GF, -GU)-7.62	—	—	1	—	300	30	B,C	2(105),4*
DFK-PC4/ X-G-7.62-LOE,or-FS4.8	—	—	1	—	300	30	B,C	2(105),4*
DFK-PC4/X-GF-7.62	—	—	1	—	300	30	B,C	2(105),4*
PCV4/ X(-G,-GF,-GU)-7.62	—	—	1	—	300	30	B,C	2(105),4*

(A) 2 Crimp barrel sizes.

(1) Followed by -ST, -STF, -STFL or -STFR.

(2) May be used at 600V where printed circuit board is conformal coated or equivalent to provide acceptable spacings at the solder pins.

(3) Multiple wire rating for field and factory-wiring of 3 No. AWG Cu. stranded wires.

Suffix "X" in the Cat. Nos. above represent a one or two-digit number.

PC4/X-G-15.24-1	—	—	1	—	600	30	B,C	2(105),4*
PC4/X-G-15.24-2	—	—	1	—	600	30	B,C	2(105),4*
PCV4/X-G-15.24-1	—	—	1	—	600	30	B,C	2(105),4*
PCV4/X-G-15.24-2	—	—	1	—	600	30	B,C	2(105),4*

Suffix "X" in the Cat. Nos. above represent a one or two-digit number.

AK4, AKG4	12-22	CU	2	7	300	20	B,C	2(105),4*
AKG16	6-18	CU	2	25	300	50(1)	B,C	2(105),4*
AKG35	2-18	CU	2	50	300	115	B,C	2(105),4*

(1) For factory-wiring, AKG16 is suitable for 65A max.

AKG4, -16, -35 are followed by suffix Black, Blue or Green/Yellow.

HDFK25(1,2),HDFKV25(1,2)	2-8	CU	2	35	600	115	B,C	2(105),4
--------------------------	-----	----	---	----	-----	-----	-----	----------

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
HDFK50(1)(3),HDFKV50(1)(3)0-6		CU	2	75	600	150	B,C	2(105),4
(1) - With or without one or more suffixes -DP, -F, -GNYE (Green/Yellow), -PE and/or -VP.								
(2) One No. 2-8 AWG Cu. str. with one No. 14AWG Cu. str. for field and factory-wiring.								
(3) One No. 2 AWG Cu. str. with one No. 8-12 AWG Cu. str. for field and factory-wiring.								
HDFK95(1),HDFKV95(1)	4/0-4	CU	2	175	600	230	B,C	2(105),4
(1) - With or without one or more suffixes -DP, -F, -GNYE (Green/Yellow), -PE and/or -VP.								
HDFK4(1),HDFKV4(1)	10-30	CU	2	5-7	300	30	B,D	2(105),4
HDFK10(1),HDFKV10(1)	6-24	CU	2	11-20	300	65	B,D	2(105),4
HDFK10HV	24-6	CU	2	11-20	600	65	B,C	2(105)
HDFK16, -GNYE(1)	4-20	CU	2	18	600	85	B,C	2(105),4
HDFKV16, -GNYE(1)	4-20	CU	2	18	600	85	B,C	2(105),4
(1) - May be followed by suffixes -GNYE (Green/Yellow) -TWIN, -TWIN-DP, and/or -VP.								
DFK-MSTB(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
DFK-MSTB(1)(2)	—	CU	1	N/A	600	15	B,D	2(105)
DFK-MSTBA(1)(4)	—	CU	1	N/A	300	15	B,D	2(105),4,*
DFK-MSTBVA(1)(4)	—	CU	1	N/A	300	15	B,D	2(105),4,*
FRONT-MSTB(1)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
FRONT-MSTB(1)(3)	30-12	CU	2	5-7	600	15	B,D	2(105)
(1) Suffixes 2.5, followed by / one or two-digit number.								
(2) Suffixes -G or -GF, w/wo WW1X1, followed by -5.08, -10.16-1, or -10.16-2.								
(3) Suffixes -ST or -STF, followed by -5.08, -10.16-1, or -10.16-2, w/wo -AU, -BK and/or -ABGY.								
(4) Suffixes -G or -GF, w/wo WW1X1, followed by -5.08.								
(5) Suffixes -ST or -STF followed by -5.08 w/wo -AU, -BK and/or -ABGX.								
MDSTB(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTB(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBV(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBV(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVA(1)(Z)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBW(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
MDSTBW(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MSTB(1)(5)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MSTB(1)(3)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTB(1B)(3)	30-12	CU	2	5.7	300	16	B,D	2(105), 4, #
MSTBP(1)(1B)(5)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MSTBP(1)(1B)(3)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTBT(1)(1B)(5)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MSTBT(1)(1B)(3)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTB(1)(8)	28-12	CU	2	5-7	600	15	B,D	2(105),4,*
MSTB(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTB(1)(1A)(7)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBA(1)(1A)(6), -THT	—	CU	1	N/A	600	15	B,D	2(105)
MSTBA(1)(1A)(7)	—	CU	1	N/A	300	15	B,D	2(105)
(1) Suffixes 2.5, followed by / one or two-digit number.								
(1A) With or without suffixes HC and/or L.								
(1B) Suffixes 2.5, followed by HC, followed by / one or two digit number.								
(2) Suffixes -G, -GF, -GFL, -GFR or -GL followed by -5.08.								
(3) Suffixes -ST, -STF or -STZ followed by -5.08 w/wo -AB, -AU, PF and/or SO.								
(4) Suffixes -G, -GFL, -GFR or -G1, followed by -10.16-1, or -10.16-2.								
(5) Suffixes -ST, -STF or -STZ, followed by -5.08, -10.16-1 or -10.6.2 w/wo -AB, -AU, PF and/or SO.								
(7) Suffixes -G, -G0.5, -GF or -GEH, followed by -5.08, w/wo -LA, LAB/RD, -KM, -H, -R, -AU, -BK, -ABGY, -A.45, -6.03.								
(8) Followed by suffix -ST-5.08, and by BGHIL S01.								
MSTBAG(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBAG(1)(1A)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBV(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
MSTBV(1)(1A)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBVW(1)(2)	—	CU	2	—	300	15	B,D	2(105),*
MSTBVA(1)(1A)(6), -THT	—	CU	1	N/A	600	15	B,D	2(105)
MSTBVA(1)(1A)(2)	—	CU	1	N/A	300	15	B,D	2(105)
A-MSTBV(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
A-MSTBV(1)(1A)(2)	—	CU	1	N/A	300	15	B,D	2(105)
A-MSTBVA(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
A-MSTBVA(1)(1A)(2)	—	CU	1	N/A	300	15	B,D	2(105)
EMSTBVA(1)-G-5.08	—	CU	1	N/A	300	15	B,D	2(105)
MSTBVAG(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBVAG(1)(1A)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBW(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBW(1)(1A)(2)	—	CU	1	N/A	300	15	B,D	2(105)
MVSTBN(1)(1B)(7)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MVSTBN(1)(1B)(8)	30-12	CU	2	5-7	300	15	B,D	2(105)
MVSTBR(1)(7)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MVSTBR(1)(8)	30-12	CU	2	5-7	300	15	B,D	2(105)
MVSTBW(1)(7)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MVSTBW(1)(8)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MVSTBR(1B)(8)	30-12	CU	2	5.7	300	16	B,D	2(105),4, #
MVSTBW(1B)(8)	30-12	CU	2	5.7	300	16	B,D	2(105),4, #

(1)-Suffixes 2,5, followed by /one or two-digit number.

(1A)With or without suffixes HC and/or L.

(1B) Suffixes 2,5, followed by HC, followed by / one or two digit number.

(2)Suffixes -G, -GB, -G0.5, -GF or -GEH, followed by -5.08, w/wo -LA, -LAB/RD, -KM, -H, -R, -RF, -RN, -AU, -BK, -ABGY, -4.45, -6.03

(6)Suffixes -G, -G0.5, -GF or -GEH, followed by -10.16.1, -10.16-2, w/wo -LA, -LAB/RD, -KM, -H, -R, -AU, -BK, -ABGY, -4.45, -6.03.

(7)Suffixes -ST or -STF, followed by -10.16-1, -10.16-2, w/wo -KM, -AU, -BK and/or -ABGY.

(8)Suffixes -ST or -STF, followed by -5.08, w/wo -KM, -AU, -BK and/or -ABGY.

SMSTB(1)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4*
SMSTB(1)(8)	30-12	CU	2	5-7	600	15	B,D	2(105),4
SMSTB(1)(7)	30-12	CU	2	5-7	600	15	B,D	2(105)
SMSTB(1)(9)	—	CU	1	N/A	600	15	B,D	2(105)
SMSTB(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
SMSTBA(1)(9)	—	CU	1	N/A	600	15	B,D	2(105)
SMSTBA(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
FK-MSTBP(1)(10)	24-14	CU	2	5-7	600	15	B,D	2(105),4
FK-MSTBP(1)(5)	24-14	CU	2	5-7	300	15	B,D	2(105)
FKC(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),4
FKC, FKCT(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105)
FKIC(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),4
FKIC(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105)
FKCVR(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),4
FKCVR(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105)
FKCVW(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),4
FKCVW(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105)
TMSTBP(1)(11)	30-12	CU	2	5-7	600	15	B,D	2(105),4
TMSTBP(1)(4)	30-12	CU	2	5-7	300	15	B,D	2(105)
MSTBO(1)(12)	—	CU	1	N/A	600	8	B,D	2(105)
MSTBO(1)(3)	—	CU	1	N/A	300	8	B,D	2(105)
MSTB2.5/2-GFL-5.08	—	CU	1	—	300	15	B,D	2(105),*
MSTB2.5/ 2-STFL-5.08	30-12	CU	2	5-7	300	15	B,D	2(105),*
MVSTBR2.5/X-STF- 10.16-1, -2	30-12	CU	2	5-7	600	10	B,C	2(105),*

(1)Suffixes 2,5, /one or two digit number.

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
(3)Suffixes -GL or -GR, followed by -5.08.								
(4)Suffixes -ST or STF followed by -5.08, w/wo -AU and/or -ABGY.								
(5)Suffixes -ST or STF, with or without -5.08 .								
(6)Suffixes -G followed by -5.08, w/wo -AU, BK, and or -AGBY.								
(7)Suffixes ST followed by -5.08, w/wo -AU, -BK, and/or -ABGY.								
(8)Suffixes -ST followed by -10.16-1, or -10.16-2, w/wo -AU, -BK and/or -ABGY.								
(9)Suffix -G, followed by -10.16-1, or -10.16-2, w/wo -AU, -BK and/or -ABGY								
(10)Suffixes -ST, -STF or -STZ followed by -10.16-1, or -10.16-2 with or without NZ:EH.								
(11)Suffixes -ST or -STF, followed by -10.16-1, or -10.16-2, w/wo -AU and/or -ABGY.								
(12)Suffixes -GL or -GR, followed by -5.08, -10.16-1, or -10.16-2.								
DFK-MSTB(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
FRONT-MSTB(1)(3)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MDSTB(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBV(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVA(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVH(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBVHA(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
MDSTBW(1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
MSTB(1)(1B)(5)	30-12	CU	2	5-7	600	15	B,D	2(105),4
MSTBP(1)(1B)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
(1)Suffixes 2.5, followed by /one or two-digit number.								
(2)Suffixes -G or -GE, w/wo WW1X1.								
(3)Suffixes -ST or -STF, w/wo -AU, -BK and/or -ABGY.								
(4)Suffixes -G, -GF or -G1.								
(5)Suffixes -ST, -STF or -STZ, w/wo -10.1 or -10.2.								
MSTBT(1)(1B)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MSTB(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBA(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBAG(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBAGKL(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBV(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBVA(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBVAG(1)(1A)(6)	—	CU	1	N/A	600	15	B,D	2(105)
MSTBW(1)(1A)(6)	—	CU	1	N/A	300	15	B,D	2(105)
(1)Suffixes 2.5, followed by /one or two-digit number.								
(1A)With or without suffixes HC and/or L.								
(1B)Suffixes 2.5 followed by HC, followed by /one or two-digit number.								
(5)Suffixes -ST, -STF or -STZ, w/wo -10.1 or -10.2.								
(6)Suffixes -G, -G0.5 or -GF, w/wo -10.1, -10.2, -LA, -LAB/RD, -R, -AU, -BK and/or -ABGY.								
MVSTBN(1)(1B)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MVSTBR(1)(1B)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MVSTBW(1)(1B)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
SMSTB(1)(8)	30-12	CU	2	5-7	300	15	B,D	2(105),4
SMSTB(1)(9)	—	CU	1	N/A	300	15	B,D	2(105)
SMSTBA(1)(9)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBO(1)(10)	—	CU	1	N/A	300	15	B,D	2(105)
FKC(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),*
FKC, FKCT(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105),*
FKIC(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),*
FK1C(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105),*
FKCVR(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),*
FKCVR(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105),*
FKCVW(1)(10)	26-12	CU	2	N/A	600	10	B,D	2(105),*
FKCVW(1)(5)	26-12	CU	2	N/A	300	10	B,D	2(105),*
(1)Suffixes 2.5, followed by /one or two-digit number.								

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
(7)Suffixes -ST or -STF, w/wo -AU, -BK and/or -ABGY, may be followed by -10-1, or 10-2.								
(8)Suffixes -ST, w/wo -AU, -BK and/or -ABGY, may be followed by -10-1, or 10-2.								
(9)Suffixes -G, w/wo -AU, -BK and/or -ABGY, may be followed by -10-1, or 10-2.								
(10)Suffixes -ST and by -G1L or -G1R.								
FRONT-GMSTB(1)(2)	30-12	CU	2	5-7	300	15	B,D	2(105),4
GMSTB(1)(3)	30-12	CU	2	5-7	600	15	B,D	2(105),4
GMSTB(1B)(3)	30-12	CU	2	5.7	300	16	B,D	2(105),4, #
GMSTBP(3)	30-12	CU	2	5-7	600	15	B,D	2(105),4
GMSTBP(5)	30-12	CU	2	5-7	300	15	B,D	2(105)
GMSTB(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTB(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTBA(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBV(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTBV(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBVA(1)(4)	—	CU	1	N/A	600	15	B,D	2(105)
GMSTBVA(1)(6)	—	CU	1	N/A	300	15	B,D	2(105)
GMSTBAS2.5/	—	CU	1	—	600	15	B,D	2(105),#

4-G-7.62

- (1)Suffixes 2.5, followed by /one or two-digit number.
- (1B) Suffixes 2.5, followed by HC, followed by / one or two digit number.
- (2)Suffixes -ST or -STF, followed by -7.62, w/wo -AU, -BK and/or -ABGY.
- (3)Suffixes -ST, w/wo -15.24, -1, -2, -AU, -BK and/or -ABGY.
- (4)Suffixes -G or -GF, w/wo -15.24, -1, -2, -LA, -R, -AU, -BK and/or -ABGY.
- (5)Suffixes -ST, w/wo -7.62, -AU, -BK and/or -ABGY.
- (6)Suffixes -G, -GF w/wo -7.62, -LA, -R, -AU, -BK and/or -ABGY.

GMVSTBR(1)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
GMVSTBW(1)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
GMVSTBR(1B)(3)	30-12	CU	2	5.7	300	16	B,D	2(105),4, #
GMVSTBR(1B)(5)	30-12	CU	2	5.7	300	16	B,D	2(105),4, #
GMVSTBW(1B)(5)	30-12	CU	2	5.7	300	16	B,D	2(105),4, #
GMVSTBR(1)(6)	30-12	CU	2	5-7	600	15	B,C	2(105),4
GMVSTBW(1)(6)	30-12	CU	2	5-7	600	15	B,C	2(105),4
UGMSTBHK(1)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
GMSTBHK(1)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
GFKC (1) -ST, -STF	22-12	CU	2	N/A	300	10	B,D	2(105),4

f/b -7.5 or -7.62

- (1)Suffixes 2.5, followed by /one or two-digit number.
- (1B) Suffixes 2.5, followed by HC, followed by / one or two digit number.
- (5)Suffixes -ST or -STF, followed by -7.62, -AU, -BK and/or -ABGY.
- (6)Suffixes -HV, followed by -ST or -ST.762 or /8-STGY3XEB2.
- (7)Suffixes /10-G, w/wo -7.62.

GIC, GICV(1)(2)	—	CU	1	N/A	300	15	B,D	2(105)
GIC, GICV(1)(3)	30-12	CU	2	5-7	300	15	B,D	2(105),4
IC, ICV, AICV (1)(4)	—	CU	1	N/A	300	15	B,D	2(105)
IC, ICV(1)(5)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MSTBH(6)	—	CU	1	N/A	300	15	B,D	2(105)
MSTBHK(6)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MSTBHKT(6)	30-12	CU	2	5-7	300	15	B,D	2(105),4

- (1)Suffixes 2.5, followed by /one of two-digit number.
- (2)Suffixes -G, -GF, followed by -7.62.
- (3)Suffixes -ST, -STF, -STGF, followed by -7.62.
- (4)Suffixes -G, -GF, followed by -5.08.
- (5)Suffixes -ST, -STF, -STGF, followed by -5.08.
- (6)Suffixes 2.5, followed by /10G, followed by -5.08.

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
UMSTBHK(6)	30-12	CU	2	5-7	300	15	B,D	2(105),4
UMSTBHKT(6)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MSTBU(1)(7)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MVSTBU(1)(8)	—	CU	1	N/A	300	15	B,D	2(105)
MVSTBU(1)(9)(11)(14)	30-12	CU	2	5-7	300	15	B,D	2(105),4
MSTBVK(1)(10)	—	CU	1	N/A	300	15	B,D	2(105)

(1) Suffixes 2.5, followed by /one of two-digit number.

(6) Suffixes 2.5, followed by /10G, followed by -5.08.

(7) Suffixes -ST, -STD, followed by -5.08, w/wo -FL.

(8) Suffixes -GB, -GFB, followed by -5.08.

(9) Suffixes -STF, followed by -5.08.

(10) Suffixes -G, -GF, followed by -5.08.

(11) -STISO CEAG, STFSO CEAG followed by -5.08.

(14) -Cat. No. MVSTBU2.5 additionally has a multiple wire rating of 2 No. 16 AWG Cu. stranded wires for field and factory-wiring.

MVSTBK(1)(11)	30-12	CU	2	5-7	300	15	B,D	2(105),4
UMSTBVK(1)(10)	—	CU	1	N/A	300	15	B,D	2(105)
UMSTBVK(1)(11)	30-12	CU	2	5-7	300	15	B,D	2(105),4
UMSTBVK2.5/ X-STF-	30-12	CU	2	5-7	600	10	B,C	2(105),*

10.16-1, -2

UMSTBVK2.5/X-GF	—	CU	1	N/A	600	10	B,C	2(105),*
SKLB(13)	—	CU	1	N/A	300	10	B,D	2(105)
SKLB(12)	30-12	CU	2	5-7	300	10	B,D	2(105),4

(1) Suffixes 2.5, followed by /one of two-digit number.

(10) Suffixes -G, -GF, followed by -5.08.

(11) Suffixes -ST, -STF, followed by -5.08.

(12) Suffixes 2.5, /12.

(13) Suffixes 2.5, /12, followed by -ST.

HCC4-F, -M	30-10	CU	2	5-7	300	15	B,C	2(105),4
UISLKG35	2-18	CU	2	18	NA	NA	B,C	2(105),4(#)
MSTBC2.5(1)	30-12	CU	1	—	300	10	B,D	2(105)*
ICC2.5(2)	30-12	CU	1	—	300	10	B,D	2(105)#
MSTBC2.5/X-STZF-	20-18/ 16-14	CU	1	N/A	600	10	B,C	2(105),*

10.16-1, -2

ICC2.5/X-STZF-	20-18/ 16-14	CU	1	N/A	600	10	B,C	2(105),*
----------------	-----------------	----	---	-----	-----	----	-----	----------

10.16-1, -2

(1) Followed by /one or two digit number suffix -ST, -STZ, -STZF or -STZFD and by -5.08.

(2) Followed by /one or two digit number, Suffix -STZ, -STZD or -STZF, and by -5.08.

(#) The terminal blocks are to be installed on the manufactures 35mm wide copper (only) mounting rails, intended for the purpose.

IDC0.5-DL(1)	20-30(2)	CU	2	—	300	5	B,D	2(105),*
IDC0.8-DP(1)	18-30(2)	CU	2	—	300	10(3)	B,D	2(105),*

(1) Followed by /one or two digit number.

(2) Factory-wiring only for wires smaller than No. 22 AWG.

(3) 7A max for field-wiring.

UGMSTBHK, GMSTBHK with suffix 2.5, followed by / 10-G,w/wo -7.62	30-12	CU	2	5-7	300	10	B,D	2(75),*
MBK5/E-T or-IG	28-12	CU	2	5-7	300	20	B,C	2(105),4
MBT2.5, -BU, -T10	30-12	CU	2	5-7	300	20	B,C	2(105),4
MBT2.5-PE	30-12	CU	2	5-7	—	—	B,C	2(105),4
UK2.5(1)	30-12	CU	2	5-7	600	20	B,C	2(105),4
UK3(1)	30-12	CU	2	5-7	300	20	B,C	2(105),4

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
UK4(1)	28-12	CU	2	5-7	600	20	B,C	2(105),4
UXKK4	28-12	CU	2	5-7	600	20	B,C	2(105),4

(1) Followed by suffix B, -MSTB-5.08, -PLUS, -T, -TG, -T-P/P or -TWIN.

UK5(1)	30-10	CU	2	5-7	300	30	B,C	2(105),4
UK10(1)	24-6	CU	2	11-20	300	65	B,C	2(105),4
UK3-TWIN-PE	301-2	CU	2	5-7	300	—	B,D	2(105),4
UK5-TWIN-PE	30-10	CU	2	5-7	—	—	B,C	2(105),4
UK10-TWIN-PE	24-6	CU	2	11-20	—	—	B,C	2(105),4
UK10-PLUS-PE	24-6	CU	2	11-20	—	—	B,C	2(105),4
UK3D-MSTBV-5.08(2)	30-12	CU	2	5-7	300	20	B,C	2(105),4
UKK3-MSTB-5.08	30-12	CU	2	5-7	300	10	B,C	2(105),4
USK4-FSR(3)	28-12	CU	2	5-7	600	20	B,C	2(105),4

(1) Followed by suffix B, -MSTB-5.08, -PLUS, -T, -TG, -T-P/P or -TWIN.

(2) With or without suffixes /EK, -LA12RD, -LA12RT, -LA24RD, -LA24RT, -LA48RD, -LA48RT, -LA60RD, -LA60RT.

(3) Followed by suffix (3-2.8-0.8) or (4-2.8-0.8).

G5(1)	26-10	CU	2	5-7	300#	30	B	2(105),4*
K2.5(2)	30-14	CU	2	5-7	300	15	B,D	2(105),4*
K3(2)	28-12	CU	2	5-7	600	20	B,C	2(105),4*
K4(2)	28-12	CU	2	5-7	600	20	B,C	2(105),4*
K4-TG(2)	28-12	CU	2	5-7	300	20	B,D	2(105),4*
K5(2)	26-10	CU	2	5-7	600	30	B,D	2(105),4*
K10(2)	26-8	CU	2	11-15	600	50	B,C	2(105),4*
K16, K16/E	24-6	CU	2	11-15	600	65	B,C	2(105),4*
K25, K25/E	22-4	CU	2	18-25	600	85	B,C	2(105),4*
K35, K35/E	18-1/0	CU	2	30-50	600	140	B,C	2(105),4*
MBK	30-14	CU	2	5-7	300	15	B,D	2(105),4*
MBK2.5/E	30-12	CU	2	5-7	300	20	B,D	2(105),4*
MBKK2.5-PE	30-12	CU	2	5-7	300	20	B,D	2(105),4*
MBK2.5/E-PE	30-12	CU	2	5-7	—	—	B,D	2(105),4*
UGSK/S	26-8	CU	2	11-15	600	50	B,2	2(105)

(1) Followed by suffixes /2, /3, /4, /6, /12, /2B.

(2) May be followed by suffixes /E, /M.

GTF76/230	26-8	CU	2	11-15	250	50	B,C	2(105)
ST-BE	14-30	CU	2	5-7	300	10	B,C	2(105),*
ST-BE-VIERPOL	14-30	CU	2	5-7	300	10	B,C	2(105),*
ST-1N4007	14-30	CU	2	5-7	300	1	B,C	2(105),*
MBK3/E-Z-PE	30-12	CU	2	5-7	—	—	B,D	2(105),4*
MBK3	28-12	CU	2	5-7	600	20	B,C	2(105),4*
MBK5, MBK5/E	26-10	CU	2	5-7	600	30	B,C	2(105),4*
MBK5/E-FS	26-10	CU	2	5-7	300	5	B,D	2(105),4*
MBK5/E-FS/FS	26-10	CU	1	—	300	—	B,D	2(105),4*
MBK10	26-8	CU	2	11-15	600	50	B,C	2(105),4*
SSK5(3)	26-10	CU	2	5-7	600	30	B,C	2(105),4*
SSK0525-TG(3)	28-12	CU	2	5-7	300	20	B,D	2(105),4*
SSK/N0525-LB1(3)	28-12	CU	2	5-7	600	20	B,C	2(105),4*
SSK110(3)	26-8	CU	2	11-15	600	50	B,C	2(105),4*
SSK116(3)	24-6	CU	2	11-15	600	65	B,C	2(105),4*
SSK125(3)	22-4	CU	2	18-25	600	85	B,C	2(105),4*
SSK135(3)	18-2	CU	2	20-50	600	115	B,C	2(105),4*
ST-Si(4)	—	CU	1	—	300	10	B,D	2(105),4*
UDK3	30-12	CU	2	5-7	300#	20	B,D	2(105),4*
UDK4	30-10	CU	2	5-7	600#	30	B,D	2(105),4*
UDK4-ILA500	30-10	CU	2	5-7	600	0.5	B,D	2(105),4*
UDK4-ILA1000	30-10	CU	2	5-7	600	1	B,D	2(105),4*
UDK4-UJA(5)	30-10	CU	2	5-7	600#	30	B,D	2(105),4*
URTK/S,	26-8	CU	2	11-15	300	50	B,D	2(105),4*
URTK/S-Ben	26-8	CU	2	11-15	300	50	B,D	2(105),4*

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
(3) May be followed by suffix Kri.								
(4) May be followed by suffixes LA250, LED12, LED24, LED60, -UK4.								
(5) May be followed by suffixes -12RD/O-U, -12RT/O-U, -24RD/O-U, -24RT/O-U, -48RD/O-U, -48RT/O-U, -60RD/O-U, -60RT/O-U, 220, -/UK.								
#Limited amp rating at max voltage of 300v or 600v.								
URTK/SP	26-8	CU	2	15	300	45	B,D	2(105),4*
URTK/S-Ben 10	26-8	CU	2	20	600	50	B,D	2(105),4*
URTK/SS	28-12	CU	2	5-7	300	20	B,D	2(105),4*
URDK6	26-8	CU	2	15	300	50	B,C	2(105), #
URTK6	26-8	CU	2	15	300	50	B,C	2(105), #
UGSK6	26-8	CU	2	15	300	50	B,C	2(105), #
MT1.5	30-14	CU	2	4	300	15	B,D	2(105),4,*
MT1.5-TWIN	30-14	CU	2	4	300	15	B,D	2(105),4,*
MT1.5-QUATTRO	30-14	CU	2	4	300	15	B,D	2(105),4,*
MT1.5-PE	30-14	CU	2	4	—	—	B,D	2(105),4,*
MTTB1.5	30-14	CU	2	4	300	15	B,D	2(105),4,*
SI-H-FKS15	N/A	CU	1	N/A	32	15	B,C	2(105),*
SI-H-FKS30	N/A	CU	1	N/A	32	30	B,C	2(105),*
MT1.5-TWIN-PE	14-30	CU	2	4	—	—	B,D	2(105)
MT1.5-QUATTRO-PE	14-30	CU	2	4	—	—	B,D	2(105)
ZFK1.5(4)	14-26	CU	2	N/A	300	—	B,C	2(105),*
ZFK1.5PE(4)	14-26	CU	2	N/A	—	—	B,C	2(105),*
ZKKB1.5(4)	26-14	CU	2	N/A	600	15	B,C	2(105),4,#
ZFK2.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105),*
ZFK2.5-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105),*
ZFK2.5-MT(4)	12-26	CU	2	N/A	300	15	B,C	2(105),*
ZDMTK2.5(4)	26-12	CU	2	N/A	300	10	B,C	2(105),*
ZDMTK2.5-TWIN(4)	26-12	CU	2	N/A	300	10	B,C	2(105),#
ZFKK2.5-MT(4)	26-14	CU	2	N/A	600	15,20	B,C	2(105),4,#
ZFK2.5-TWIN(4)	12-26	CU	2	N/A	600	20	B,C	2(105),*
ZFK2.5-TWIN-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105),*
ZFK12.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105),*
ZFK12.5-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105),*
ZFDK2.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105),*
ZFDK2.5-MT(4)	12-26	CU	2	N/A	300	15	B,C	2(105)
(4) All may be followed by suffix BU.								
ZFDK2.5-PE(4)	12-26	CU	2	N/A	—	—	B,C	2(105),*
ZFKKB2.5(4)	12-26	CU	2	N/A	600	20	B,C	2(105),*
ZFK4(4)	10-24	CU	2	N/A	600	30	B,C	2(105),*
ZFK4-PE(4)	12-24	CU	2	N/A	—	—	B,C	2(105),*
ZFK4-TG(4)	10-24	CU	2	N/A	600	15	B,C	2(105),*
ZFK4-HESI	10-24	CU	2	N/A	600	10	B,C	2(105),4*
ZFK4-HESILED	10-24	CU	2	N/A	600	10	B,C	2(105),4*
ZFK4-HESILA	10-24	CU	2	N/A	600	10	B,C	2(105),4*
ZGSK4	24-10	CU	2	N/A	300	30	B,C	2(105),4*
ZRTK4	24-10	CU	2	N/A	300	30	B,C	2(105),4*
ZFK14(4)	10-24	CU	2	N/A	600	30	B,C	2(105),*
ZFK14-PE(4)	12-24	CU	2	N/A	—	—	B,C	2(105),*
ZFK4-TWIN(4)	24-10	CU	2	N/A	600	30	B,C	2(105),4,#
ZFK4-TWIN-PE(4)	24-10	CU	2	N/A	—	—	B,C	2(105),4,#
ZFKK4(4)	24-10	CU	2	N/A	600	30	B,C	2(105),4,#
ZFKD4-PE(4)	24-12	CU	2	N/A	—	—	B,C	2(105),4,#
ZFKKB4(4)	24-10	CU	2	N/A	600	30	B,C	2(105),4,#
ZFK6(4)	20-8	CU	2	N/A	600	50	B,C	2(105),4,#
ZFK6-DREHSI(5X20)(4)	20-8	CU	2	N/A	600	20	B,C	2(105),4,#
ZFK6-DREHSI(6.3X32)(4)	20-8	CU	2	N/A	600	20	B,C	2(105),4,#
(4) All may be followed by suffix BU.								

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
ZFK6-PE	8-20	CU	2	N/A	600	N/A	B,C	2(105),4,#
ZFK6(4)	20-8	CU	2	N/A	600	50	B,C	2(105),4,#
ZFK6-DREHSI(5X20)(4)	20-8	CU	2	N/A	600	20	B,C	2(105),4,#
ZFK6-DREHSI(6.3X32)(4)	20-8	CU	2	N/A	600	20	B,C	2(105),4,#
ZFKDS(1)	26-12	CU	2	N/A	300	10	B,C	2(105),*
ZFKDSA1.5-7.62(4)	26-12	CU	2	N/A	300	10	B,C	2(105),*
ZFKKDS(1)	12-26	CU	2	N/A	300	10	B,C	2(105),*
ZFKKDSA(1)	12-26	CU	2	N/A	300	10	B,C	2(105),*
ZFK3DS(1)	12-26	CU	2	N/A	300	10	B,C	2(105),*
ZFK3DSA(1)(3)	12-26	CU	2	N/A	300	10	B,C	2(105),*
ZFK3DS1.5/18-BK	26-12	CU	2	N/A	300	10	B,C	2(105),#

5650288

(1) Followed by suffixes 1.5, -5.08, or -6.08 all may be followed by suffix BU.

(2) All Cat. Nos. are with or without suffixes -F, -M, -NS35, all may be followed by suffix BU.

(3) May be followed by suffix -DS, all may be followed by suffix BU.

(4) All may be followed by suffix BU.

ZFK3DS1.5/18-BK	26-12	CU	2	N/A	300	10	B,C	2(105),#
5650288								
ZFK4DS1.5-5.08	26-12	CU	2	N/A	300	10	B,C	2(105),*
ZFK4DSA1.5-6.08	26-12	CU	2	N/A	300	10	B,C	2(105),*
MZB1.5(2)	26-14	CU	2	N/A	600	15	B,C	2(105),#
MZDB1.5(2)	26-14	CU	2	N/A	600	15	B,C	2(105),#
MZFK1.5(4)	26-14	CU	2	N/A	600	15	B,C	2(105),#
MZFK1.5-PE(4)	26-14	CU	2	N/A	N/A	N/A	B,C	2(105),4,#
MZB1.5-PE(4)	26-14	CU	2	N/A	N/A	N/A	B,C	2(105),#
MZB1.5-NS35-PE(4)	26-14	CU	2	N/A	N/A	N/A	B,C	2(105),#
ZFK6(5)	20-8	CU	2	N/A	600	20	B,C	2(105),#
ZEC1.0 (7)	26-16	CU	2	N/A	300	8	D	2(105),#
ZEC1.5 (8)	26-14	CU	2	N/A	300	10	B,D	2(105),#
ZEC1.5/5-ST-7.5	26-14	CU	2	N/A	600	10	B,D	2(105),#

with suffixes

NZ:292416,

NZ:292417

(1) Followed by suffixes 1.5 and -5.08.

(2) All Cat. Nos. are with or without suffixes -F, -M, -NS35, all may be followed by suffix BU.

(3) May be followed by suffix -DS.

(4) All may be followed by suffix BU.

(5) Followed by suffixes -DREHSILED24 or -FREHSILSA250 and by (5x20) or (6.3x32).

(7) Followed by /1 or /2 digit number, followed by -ST-3.5C1R1 and a 1 or 2 digit number.

(8) Followed by /1 or /2 digit number, followed by -ST, -5.0 or -7.5 C1, followed by Suffix C2 R1 and a 1 or 2 digit number.

ZDIK1.5(6)	26-14	CU	2	N/A	300	15	B,C	2(105),#
ZVIOK1.5(6)	26-14	CU	2	N/A	300	15	B,C	2(105),#
ZFKK1.5-MSTBV-5.08	26-14	CU	2	N/A	300	15	B,C	2(105),#
ZFKK1.5-MSTBV-5.08-PE/F26-14		CU	2	N/A	Ground- ing	N/A	B,C	2(105),#
ZFKK1.5-ICV-5.08	26-14	CU	2	N/A	300	15	B,C	2(105),#
ZFKK1.5-ICV-5.08-PE/F	26-14	CU	2	N/A	—	—	B,C	2(105),4
ZFK1.5-TWIN(4)	26-14	CU	2	N/A	300	15	B,C	2(105),#
ZFKDS2.5-5.08	26-12	CU	2	N/A	300	10	B,C	2(105),4,*
ZFKDS2.5-5.08-L	26-12	CU	2	N/A	300	10	B,C	2(105),4,*
ZFKDSA2.5-6.08-R	26-12	CU	2	N/A	300	10	B,C	2(105),4,*
ZFKKDS2.5-5.08	26-12	CU	2	N/A	300	10	B,C	2(105),4,*
ZFKKDS2.5-5.08-L	26-12	CU	2	N/A	300	10	B,C	2(105),4,*
ZFKKDS2.5-6.08-R	26-12	CU	2	N/A	300	10	B,C	2(105),4,*
ZFDK1.5(4)	26-14	CU	2	N/A	300	15	B,C	2(105),#
ZFKK1.5(4)	26-14	CU	2	N/A	300	15	B,C	2(105),#
ZFKDS1(7)	26-16	CU	2	N/A	300	10	B,C	2(105),#

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
ZFKDSA1(7)	26-16	CU	2	N/A	300	10	B,C	2(105),#
ZFK1.5-TWIN-PE	26-14	CU	2	N/A	—	—	B,C	2(105),#
ZFKDS1.5C-5.0	26-12	CU	2	N/A	300	10	B,C	2(105),#
ZFKDSA1.5C-6.0	26-12	CU	2	N/A	300	10	B,C	2(105),#
ZFKKDS1.5C-5.0	26-12	CU	2	N/A	300	10	B,C	2(105),#
ZFKKDSA1.5C-5.0L	26-12	CU	2	N/A	300	10	B,C	2(105),#
ZFKKDS1.5C-6.0R	26-12	CU	2	N/A	300	10	B,C	2(105),#
ZFDK1.5-PE	26-14	CU	2	N/A	—	—	B,C	2(105),#
MZFKK1.5	24-14	CU	2	N/A	600	15	B,C	2(105)
MZFKK1.5-PV	24-14	CU	2	N/A	600	15	B,C	2(105)
MZFKKB1.5	26-14	CU	2	N/A	600	15	B,C	2(105),#
MZFKK1.5	26-14	CU	2	N/A	600	15	B,C	2(105),#
ZPV1.5/2.5(8/1)	24-10	CU	2	N/A	300	15	B,D	2(105),4,#
ST4	20-10	CU	2	N/A	600	30	B,C	2(105),4,*
ST4-TWIN	20-10	CU	2	N/A	600	30	B,C	2(105),4,*
ST4-QUATTRO, -U	20-10	CU	2	N/A	600	30	B,C	2(105),4,*
STTB4	20-10	CU	2	N/A	300	30	B,C	2(105),4,*
STTB4-PV	20-10	CU	2	N/A	N/A	N/A	B,C	2(105),4,*
ST4-PE	20-10	CU	2	N/A	N/A	N/A	B,C	2(105),4,*
ST4-TWIN-PE	20-10	CU	2	N/A	N/A	N/A	B,C	2(105),4,*
ST4-QUATTRO-PE	20-10	CU	2	N/A	N/A	N/A	B,C	2(105),4,*
STS4-TWIN, STS4, -BU, STS4-QUATTRO	20-10	CU	2	N/A	600	30	B,C	2(105),4,#
STS4-TWIN-PE, STS4-PE, STS4-QUATTRO-PE	20-10	CU	2	N/A	—	—	B,C	2(105),4,#
ST4-HESI (5x20)	24-10	CU	2	N/A	300	6.3	B,C	2(105),4
ST4-HESILED 24	24-10	CU	2	N/A	300	6.3	B,C	2(105),4
ST4-HESILED 60	24-10	CU	2	N/A	300	6.3	B,C	2(105),4
ST4-HESILA 250	24-10	CU	2	N/A	300	6.3	B,C	2(105),4
(4)All may be followed by surrix BU.								
(6)Followed by Suffixes -LA24RD/O-M or -LA24GN/O-M.								
(7)Followed by Suffixes -V and/or -W, and by -3.81 or -6.35.								
ST1.5	26-14	CU	2	N/A	300	15	B,C	2(105),*
STTB1.5, -PV	26-14	CU	2	N/A	300	15	B,C	2(105),*
ST1.5QUATTRO	26-14	CU	2	N/A	300	15	B,C	2(105),*
ST1.5-TWIN	26-14	CU	2	N/A	300	15	B,C	2(105),*
ST1.5-PE	26-14	CU	2	N/A	—	—	B,C	2(105),*
ST1.5-QUATTRO-PE	26-14	CU	2	N/A	—	—	B,C	2(105),*
STTB4-PE	20-14	CU	2	NA	—	—	B,C	2(105),4
ST1.5-TWIN-PE	26-14	CU	2	NA	—	—	B,C	2(105),*
ZFKDS4-7.5/X	24-10	CU	2	N/A	300/ 300(1)	30	B,C	2(105),*
ZFKDS4-9	24-10	CU	2	N/A	300/ 300(1)	30	B,C	2(105),*
ZFKDS4-10/X	24-10	CU	2	N/A	300/ 600(2)	30	B,C	2(105),*
ZFKDS4-12.5/X	24-10	CU	2	N/A	600	30	B,C	2(105),*
ST4/FSI/C	24-10	CU	2	N/A	300	30	B,C	2(105),4
ST4/FSI/C-LED12	24-10	CU	2	N/A	300	30	B,C	2(105),4
ST4/FSI/C-LED24	24-10	CU	2	N/A	300	30	B,C	2(105)
(1)Limited VA 10A max for 300V general industrial use.								
(2)Limited VA 5A max for 600V general industrial use.								
MKKDS1.5(1)	14-30	CU	2	5.0	300	10	B,D	2(105)
MKKDS3(1)(3)	12-30	CU	2	5-7	300	15	B,D	2(105)
MKKDSW3(1)	12-30	CU	2	5-7	300	20	B,D	2(105)

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
MKKDSH3(1)	12-30	CU	2	5-7	300	20	B,D	2(105)
MK3DS3(1)(3)	12-30	CU	2	5-7	300	20	B,D	2(105)
MK3DS1.5(1)	14-30	CU	2	5.0	300	10	B,D	2(105)
MK3DS1.5(4)	14-30	CU	2	5.0	300	10	B,D	2(105)
MK4DS1.5(4)	14-30	CU	2	5.0	300	10	B,D	2(105)
MK3DS3/18(2)	12-30	CU	2	5-7	300	10	B,D	2(105)
MKKDSG3(1)(3)	12-30	CU	2	5-7	300	10	B,D	2(105)

(1) May be followed by suffixes /2, or /3, and/or -5.08.

(2) Followed by -36 or -52, and -5.08 AB.

(3) Multiple wire combination for field and factory-wiring, 2 No. 16 AWG sol/str. Solid and stranded wires are not intermixed.

(4) Followed by suffixes /2, or /3, and by -5.08, with or without suffixes -A-GNYE, -BC, OR -BCD.

MK3DSH3(1)	12-30	CU	2	5-7	300	15	B,D	2(105),*
MK3DSMH3(1)	12-30	CU	2	5-7	300	15	B,D	2(105),*

(1) May be followed by suffixes /2, /3, and/or -5.08.

G10/2 thru /5	6-24(A)	CU	2	11-20	600	65	B,C	2(105)
---------------	---------	----	---	-------	-----	----	-----	--------

(A) Additional wire rating of 2 No. 8 AWG Cu. str., 65A max. factory wiring only.

KDS10	24-6	CU	2	11-15	300	65	B,C,D	2(105),*
KDS10/SO	24-6	CU	2	11-15	300	65	B,C,D	2(105),*
KDS10-PE	24-6	CU	2	11-15	—	—	B,C,D	2(105),*
KDS10-PE/SO	24-6	CU	2	11-15	—	—	B,C,D	2(105),*
FRONT2.5H	12-30	CU	2	5-7	300	10	B,D	2(105),4,#
FRONT2.5H-SA5	12-30	CU	2	5-7	300	10	B,D	2(105),4,#
FRONT1.5-V-3.81	14-30	CU	2	2.5	300	10	B,D	2(105),4
FRONT2.5H-SA10	12-30	CU	2	5-7	300	10	B,D	2(105),4#
FRONT2.5V	12-30	CU	2	5-7	300	10	B,C	2(105),4#
FRONT2.5V-SA5	12-30	CU	2	5-7	300	10	B,D	2(105),4#
FRONT2.5V-SA10	12-30	CU	2	5-7	300	10	B,D	2(105),4#
EP-FRONT 25-H/ SA10	12-30	CU	2	5-7	300	10	B,D	2(105),4#
EP-FRONT2.5-H(2)	12-30	CU	2	5-7	300	10	B,D	2(105),4#
FRONT4H-6.35	10-24	CU	2	6.5-7	300	30	B,D	2(105),4
FRONT4V-6.35	10-24	CU	2	6.5-7	300	30	B,D	2(105),4
FRONT4H-7.62	10-24	CU	2	6.5-7	300	30	B,D	2(105),4
FRONT4V-7.62	10-24	CU	2	6.5-7	300	30	B,D	2(105),4

(2) Followed by SA10/4BK.

#Denotes optional suffix -5.08.

UK-FRONT4	10-24	CU	2	6.5-7	300	30	B,D	2(105),4
UK-FRONT4-PE	10-24	CU	2	6.5-7	—	—	B,D	2(105),4
FRONT-SFL2.5(1)	12-30	CU	2	6.5-7	300	4	B,D	2(105),4
IDC0.3/X-3.81	22-28	CU	2	N/A	300	5	B,C	2(130),4
USEN14	2-20	CU	2	35-40	600	16	B,C	2(105),4
USEN18	2-20	CU	2	35-40	600	63	B,C	2(105),4
QT1.5, -BU, -MT, -TG	16-22	CU	2	N/A	600	10	B,C	2(130),*
QT1.5-PE	16-22	CU	2	N/A	600	10	B,C	2(130),*
QT1.5-TWIN, -BU	16-22	CU	2	N/A	600	10	B,C	2(130),*
QT1.5-TWIN-PE	16-22	CU	2	N/A	N/A	N/A	B,C	2(130),*
QT2.5	14-18	CU	2	N/A	600	15	B,C	2(105),4
QT2.5-BU, -MT	14-18	CU	2	N/A	600	15	B,C	2(105),4
QT2.5-PE	14-18	CU	2	N/A	600	15	B,C	2(105),4
QT2.5-TG	14-18	CU	2	N/A	600	15	B,C	2(105)
QT2.5-TWIN	14-18	CU	2	N/A	600	15	B,C	2(105),4
QT2.5-TWIN-BU	14-18	CU	2	N/A	600	15	B,C	2(105),4
QT2.5-TWIN-PE	14-18	CU	2	N/A	600	15	B,C	2(105),4
QTU1.5/4	(@)	CU	2	5-7	600	10	B,C	2(105),#
QTU1.5/4-PE	(@)	CU	2	5-7	N/A	N/A	B,C	2(105),#
QTUB1.5/4	(@)	CU	2	5-7	600	10	B,C	2(105),#
QTU2.5/4	(@@)	CU	2	5-7	600	15	B,C	2(105),#

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
QTU2.5/4-PE	(@@)	CU	2	5-7	N/A	N/A	B,C	2(105),#
QTTUB2.5/4	(@@)	CU	2	5-7	600	15	B,C	2(105),#

(@) - Input side (IDC) wire range is No. 24-16 AWG Cu. str.; Output side (pressure screw) is rated No. 26-10 AWG Cu. sol/str.

(@@) - Input side (IDC) wire range is No. 24-14 AWG Cu. str.; Output side (pressure screw) is rated No. 26-10 AWG Cu. sol/str.

FK-MPT 0.5(A)	20-28	CU	2	N/A	300	4	B,C	2(105),*
FK-MPT 0.5(B)	—	CU	1	N/A	300	4	B,C	2(105),*
CPT0.5/X-M-3.5	—	CU	1	N/A	300	4	B,C	2(105),*

(A) Followed by /1 or /2-digit number, w/wo -ST, followed by -3.5 w/wo -H.

(B) Followed by /1 or /2-digit number, followed by -IC or -ICV and -3.5.

(1) Followed by suffixes /D32, /F32, /F48 with or without /ZB, or /ZD.

#(1) With or without prefix U.

#(2) Followed by suffix -FS, -FS/FS, -LOe, -LOe/LOe, -LOeR, may be followed by suffix L/B1, L/C1, may be followed by kri.

#(3) May be followed by SMDBK, -3.5, -3.81, -5.06, -6.35, -9.5.

#(4) Followed by 2 or 3, followed by suffix H, S, SH, V, VS with or without -7.5.

#(5) Followed by suffix FS, FSL.

#(6) Max. rating 15A (factory), 10A (field).

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
QTS1.5/4 (1)	(1)	CU	2	N/A	600	10	B,C	2(105), #
QTS1.5/4-PE (1)	(1)	CU	2	N/A	600	10	B,C	2(105), #
QTS2.5/4 (2)	(2)	CU	2	N/A	600	15	B,C	2(105), #
QTS2.5/4-PE (2)	(2)	CU	2	N/A	600	15	B,C	2(105), #

Note: (1) Input side (IDC) wire range is No. 24-16 AWG Cu. Str.; Output side Cage Spring wire range is No. 24-10 AWG Cu. sol/str.

Note: (2) Input side (IDC) wire range is No. 18-14 AWG Cu. Str.; Output side Cage Spring wire range is No. 24-10 AWG Cu. sol/str.

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
FK-MC0.5(1)	28-20	CU	2	N/A	150	4	B	2(105),*
MC0.5(2)	—	CU	1	N/A	150	4	B	2(105),*
MCD0.5	—	CU	1	N/A	125	4	B	2(105),9
MCDV0.5	—	CU	1	N/A	125	4	B	2(105),9
QC1(2)	18-22	CU	2	N/A	300	10	B,C	2(105),4

(1) Followed by /1 or /2 digit numbr, followed by -ST and -2.5.

(2) Followed by /1 or 2-digit number, -St, -ST-BUS or -STF, and by suffix -5.05.

(8) Followed by /1 or /2 digit numbr, followed by -G and -2.5.

(9) Followed by /1 or /2 digit numbers, followed by suffix -G1-2.5.

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
ME17.5 (1), ME22.5(1)	30-12	CU	2	5-7 (2)	300	8	B,D	2(105), #

4 (3)

(1) Followed by Suffixes UT (L or R) BUS/5, or UT (L or R) BUS/10, and by Suffixes OT-MSTBO, or OT-MKDSO, may be followed by AA to ZZ inclusive.

(2) Top terminals (MSTBT2.5, MKDSO2.5 blocks)

(3) Bottom terminals (MKCVR1.5 block)

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
ST2.5	26-12	CU	2	N/A	600	20	B,C	2(105),4,#
ST2.5-TWIN	26-12	CU	2	N/A	600	20	B,C	2(105),4,#
ST2.5-QUATTRO, -U	26-12	CU	2	N/A	600	20	B,C	2(105),4,#
ST2.5-DIO/L-R, -DIO/R-L	26-12	CU	2	N/A	600	1	B,C	2(105),*
ST2.5-TWIN-DIO/ L-R, -DIO/R-L	26-12	CU	2	N/A	600	1	B,C	2(105),*
ST2.5-QUATTRO-DIO/L-R, -DIO/R-L	26-12	CU	2	N/A	600	1	B,C	2(105),*
STTB2.5-LA24, -LA60	26-12	CU	2	N/A	600	20	B,C	2(105),*
STTB2.5	26-12	CU	2	N/A	600	20	B,C	2(105),4,#
STTB2.5-PV	26-12	CU	2	N/A	600	20	B,C	2(105),4,#

Cat. No.	Wire Size	Wire Type	FW	TQ Lb In.	V	A	UG	CA
ST2.5-PE	26-12	CU	2	N/A	N/A	N/A	B,C	2(105),4,#
ST2.5-TWIN	26-12	CU	2	N/A	N/A	N/A	B,C	2(105),4,#
ST2.5-QUATTRO-PE	26-12	CU	2	N/A	N/A	N/A	B,C	2(105),4,#
STS2.5-TWIN, STS2.5, -BU	26-12	CU	2	N/A	600	20	B,C	2(105),4,#
STS2.5-QUATTRO STS2.5-TWIN-PE, STSA.5PE	26-12	CU	2	N/A	—	—	B,C	2(105),4,#
STS2.5-QUATTRO-PE								
STTB2.5-DIO/U-O	26-12	CU	2	N/A	600	1	B,C	2(105),4
STTB2.5-DIO/O-U	26-12	CU	2	N/A	600	1	B,C	2(105),4
STTB2.5-DIO/ UL-UR	26-12	CU	2	N/A	600	20(1)	B,C	2(105),4
STTB2.5-2DIO/ O-UL/UR-UL	26-12	CU	2	N/A	600	1	B,C	2(105),4
STTB2.5-DIO/ O-UL/O-UR	26-12	CU	2	N/A	600	1	B,C	2(105),4
STTB2.5-LA230	26-12	CU	2	N/A	600	20	B,C	2(105),4
SP2.5/X, SPB2.5/X, SPDB2.5/X	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
ST2.5/1P	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
ST2.5QUATTRO/ 2P/X	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
STTB2.5/2P	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
STTB2.5/2P-PV	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
STTB2.5/2P-DIO/ O-U	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
ST2.5-3L	26-12	CU	2	N/A	300	20	B,D	2(105),4*
ST2.5-3PV	26-12	CU	2	N/A	300	20	B,D	2(105),4*
ST2.5-3PE	24-12	CU	2	N/A	N/A	N/A	B,D	2(105),4*
ST2.5-PE/3L	24-12	CU	2	N/A	600	20	B,D	2(105),4*
STTB2.5-PE	26-12	CU	2	N/A	N/A	N/A	B,D	2(105),4*
ST2.5/1P-PE	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
ST2.5-QUATTRO/ 2P-PE	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
STTB2.5/2P-PE	26-12	CU	2	N/A	300/600	20(2)	B,D	2(105),*
ST2.5-PE/L/L, ST2.5-PE/L/N	26-12	CU	2	N/A	300(3)	20(3)	B,C	2(105),4
ST2.5-MT	12-26	CU	2	N/A	600	16	B,C	2(105),4
ST2.5-TWIN-MT	12-26	CU	2	N/A	600	16	B,C	2(105),4
ST2.5-QUATTRO-MT	12-26	CU	2	N/A	600	16	B,C	2(105),4

(3) Ampere and voltage rating not applicable for lower level grounding terminals.

STTB2.5	12-26	CU	2	N/A	300	20	B,D	2(105),4
STTB2.5-PV	12-26	CU	2	N/A	300	20	B,D	2(105),4
STTB2.5-PE	12-26	CU	2	N/A	N/A	N/A	B,D	2(105),4

(1) 1 ampere for lower level terminals.

(2) 5A max. at 600V; 10A max. at 300V general industrial use.

DK-BIC-35	2-20	CU	2	40	600	100	B,C	2(105),4,*
-----------	------	----	---	----	-----	-----	-----	------------

Cat. Nos.	Wire Sizes	WT	FW	Torque In. Lb.	Volts	Amp	Use Group	CA
AKG4-GNYE	22-12	CU	2	7	—	—	B,C	2(105),4,*
AK4, AKG4-BK AKG4-BU	22-12	CU	2	7	300	20	B,C	2(105),4,*
AKG16-BK, AKG16-BU	6-18	CU	2	25	300	65	B,C	2(105),4,*
AKG16-GNYE	6-18	CU	2	25	—	—	B,C	2(105),4,*
AKG35-BK,	2-18	CU	2	50	300	115	B,C	2(105),4,*

Cat. Nos.	Wire Sizes	WT	FW	Torque In. Lb.	Volts	Amp	Use Group	CA
AKG35-BU								
AKG35-GNYE	2-18	CU	2	50	—	—	B,C	2(105),4,*
QC0.5(1)-ST-3.81	22-20	CU	2	N/A	300	6	B,C	2(105),4,#
QC0.5(1)-STF-3.81	22-20	CU	2	N/A	300	6	B,C	2(105),4,#
(1) Followed by /1 or /2-digit number.								
ST6, -BU, -TWIN	20-8	CU	2	N/A	600	50	B,C	2(105),4
ST6-PE, -TWIN-PE	20-8	CU	2	N/A	N/A	N/A	B,C	2(105),4
ST10, -BU	16-6	CU	2	N/A	600	65	B,C	2(105),*
ST10-PE	16-6	CU	2	N/A	—	—	B,C	2(105),*
ST16, -BU	16-4	CU	2	N/A	600	65	B,C	2(105),*
ST16-PE	16-4	CU	2	N/A	—	—	B,C	2(105),*
PC6(1), PCU6(1)	20-8	CU	2	11-15	600	41	B,C	2(115),4
PC6(2), PCV6(2)	—	CU	1	—	300	41	B,C	2(115),#

(1) Followed by /1-digit number, and by Suffix -ST, -STD, or -STF, followed by -10.16.

(2) Followed by /1-digit number, and by Suffix -G or -GE, followed by -10.16, with or without Suffix CODED.

FRONT-ZFL 1.5/D32	24-16	CU	2	N/A	300	4	B,C	2(120),4
ME17.5, ME22.5, ME35,	12-30	CU	1(a)	5-7	300	20	B,C	2(105),#
ME45 suffixes UT (w/wo L or R), UT/FE, F-UT (w/wo L or R), or F-UTG (w/wo L or R), foll. by suffixes BUS/5, BUS/10, BUS/5+2, BUS/10+2, w/wo suffixes AA-ZZ incl.								
ME17.5, ME22.5, ME35,	12-30	CU	1(a)	5-7	300	20	B,C	2(105),#
ME45 suffixes OT-MSTBO, OT-MKDSO, OT-1MSTBO, OT-MSTBO-SET or OT-MKDSO-SET w/wo suffixes AA-ZZ incl.								

All Cat. Nos. may be followed by a two to four character suffix (any combination of letters and/or numbers) designating nonelectrical variations such as color, customer identification, packaging or plating options.

/X One or two digit number.

(a) - Field wiring for MSTBT2.5 or MKDSO2.5 terminals.

Marking: Company name or trademark ~~DISSE~~ catalog and type designation.

See General Information Preceding These Recognitions

For use only in equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.