

supply busbars and distribution blocks

SUPPLY BUSBARS FROM 63 TO 90 A

<p>• Isc peak 17 kA</p>	Lenght	Universal 1-pole + neutral or 1-pole	2-pole	2-pole balanced on 3-phase	3-pole	4-pole
	Prong-type					
	1 row	4 049 26	4 049 38	4 049 40	4 049 42	4 049 44
	meter	4 049 37	4 049 39	4 049 41	4 049 43	4 049 45
	Fork-type					
	1 row	4 049 11	-		4 049 17	-
meter	4 049 12	4 049 14		4 049 18	4 049 20	

DISTRIBUTION TERMINAL BLOCKS FROM 63 TO 100 A

<p>• Isc peak 10 kA</p>	Number of outputs	Bar terminal blocks		Insulated terminal blocks IP 2X (XXB)		
		with screws	on support	black	blue	green
	4	0 048 01	0 048 20	0 048 50	0 048 40	0 048 30
	6			0 048 16	0 048 15	
	8	0 048 03	0 048 22	0 048 52	0 048 42	0 048 32
	12		0 048 24	0 048 54	0 048 44	0 048 34
	14	0 048 05				
	16		0 048 25		0 048 45	0 048 35
	19	0 048 06			0 048 46	0 048 36
	21		0 048 26			
24	0 048 07					
33		0 048 28		0 048 48	0 048 38	

MODULAR DISTRIBUTION BLOCKS FROM 40 TO 250 A

<p>• Isc peak 14.5 to 42 kA</p>	Admissible maximum rating (A)	2-pole			4-pole			Terminal blocks IP 2X		
		Number and section of flexible conductors (mm ²)			Number and section of flexible conductors (mm ²)			Additional outputs		
		Cat.Nos	Inputs	Outputs	Cat.Nos	Inputs	Outputs	Earth	Neutral	(mm ²)
	40	0 048 81	2 x 10	11 x 4	0 048 85	2 x 10	11 x 4	0 048 34	0 048 44	12 x 6
	100	0 048 80	2 x 16	5 x 10	0 048 84	2 x 16	5 x 10	0 048 32	0 048 42	8 x 6
	125	0 048 82	2 x 25	2 x 16 + 11 x 10	0 048 86	2 x 25	2 x 16 + 7 x 10	0 048 35	0 048 44	12 x 6
		0 048 88			0 048 88	2 x 25	2 x 25 + 11 x 10		0 048 45	16 x 6
	160				0 048 76	1 x 35	1 x 25 + 1 x 16 + 14 x 10		0 048 46	21 x 6
					0 048 79	1 x 70	2 x 25 + 4 x 16 + 8 x 10		0 048 45	16 x 6
	250				0 048 77	1 x 120	1 x 35 + 2 x 25 + 2 x 16 + 6 x 10			

SINGLE POLE MODULAR DISTRIBUTION BLOCKS AND DISTRIBUTION TERMINALS FROM 125 TO 250 A

<p>• Isc peak 27 to 60 kA</p>	Admissible maximum rating (A)	Cat.Nos	Number and section of conductors per pole (mm ²)		
			Inputs	Outputs	
	125	0 048 71		4 x 35	12 x 10
	160	0 048 83		1 x 50 (flexible bar 13 mm max.)	3 x 25 + 2 x 16 + 7 x 10
		0 048 67 (distribution terminal)		Direct into the downstream terminal	6 x 25
250	0 048 73		1 x 120 (flexible bar 16 mm max.)	6 x 25 + 4 x 10	
	0 048 68 (distribution terminal)		Direct into the downstream terminal	4 x 35 + 2 x 25	

POWER DISTRIBUTION BLOCKS FROM 125 TO 400 A

<p>• Isc peak 20 to 75 kA</p>	Admissible maximum rating (A)	Extra-flat		Stepped			
		Number and section of conductors per pole (mm ²)		Number and section of conductors per pole (mm ²)			
		Cat.Nos	Inputs	Outputs	Cat.Nos	Inputs	Outputs
	125	0 374 47	1 x 35	10 x 16 (Ph) 17 x 16 (N)	0 373 95	4 bars 12 x 4 mm receiving 5 connectors 2 x 10 each	
					0 374 30	1 x 35	5 x 25
	160				0 374 31	1 x 70	5 x 35
250	0 374 00	1 x 150	1 x 70 or 1 x 50 + 1 x 35 or 2 x 35	0 374 35	1 x 120	5 x 50	
400				0 373 08	2 x Ø8.5 mm	21 holes M6 70 mm ² max. connectors	
				0 374 42	2 x 185	15 holes M6 15 holes M8	

Red catalogue numbers: New products