

Control panel, 24VDC, 7 Inches PCT-Display, 1024x600 pixels, 2xEthernet, 1xRS232, 1xRS485, 1xCAN, 1xSD card slot, PLC function can be fitted by user



Part no. XV-303-70-C00-A00-1B
179648
EL Number 4501304
(Norway)

Product name	Eaton XV-303 Touch panel
Part no.	XV-303-70-C00-A00-1B
EAN	7640130098596
Product Length/Depth	196 millimetre
Product height	51 millimetre
Product width	135 millimetre
Product weight	0.78 kilogram
Certifications	UL File No.: E205091 CE DNV GL UL 61010-2-201 CUL UL IEC/EN 61131-2 Certified by UL for use in Canada EMC according to 2014/30/EU EN 50178
Product Tradename	XV-303
Product Type	Touch panel
Product Sub Type	None
Catalog Notes	11.9 W for basic device + 2.5 W for USB module Can be fitted by user with article no. 181585 LIC-PLC-A Heat dissipation with power consumption for 24 V License certificates for onboard interfaces not required Optionally with SD card -> article no. 181638
Enclosure material	Insulated material
Features	Integrated Runtime visualization software license Ethernet interface RS232 CAN Portrait format USB device Slot for SD card Fanless CPU and system cooling, natural convection-based passive cooling Target and web visualization RS485 USB Host Operating System Windows Embedded Compact 7 pro
Fitted with:	1 x RS232 (built-in interface) SW interfaces 1 x USB device (built-in interface) Message system (incl. buffer and confirmation) 1 x CANopen®/easyNet (built-in interfaces) Recipes Printer output Color display 1 x RS485 (built-in interface) Message indication 1 x USB host 2.0 (built-in interface) 2 x Ethernet 10/100 Mbps (built-in interface)
Functions	Additional software components, loadable Process value representation (output) possible Process default value (input) possible
Battery runtime	Back-up of real-time clock: BR 2330, non-replaceable (soldered)
Degree of protection	NEMA 4X NEMA 12 IP20, rear (according to EN 60529-1)
Degree of protection (front side)	NEMA 12 IP65
Fuse type	Built-in fuse (not accessible)

Lifespan		50,000 h (Service life of back-lighting)
Model		Plastic enclosure and glass panel in plastic frame
Mounting method		Flush mounting - Clearance: Width x Height x Depth \geq 30 mm (1.18") Flush mounting - Inclination from vertical: $\pm 45^\circ$ (if using natural convection) Flush mounting
Potential isolation		Power supply: no
Protection against polarity reversal		Yes, for supply voltage (Siemens MPI optional)
Product category		HMI-PLC (SPS function, retrofittable)
RoHs conformity		Yes
Software		XSOFT-CODESYS, Visualisation software, Engineering XSOFT-CODESYS-3, PLC-Programming software, Engineering GALILEO, Visualisation software, Engineering XSOFT-CODESYS-2, PLC-Programming software, Engineering
Type		Control panel with 2nd Ethernet port
Voltage type		DC
Shock resistance		15 g, 11 ms, Mechanical
Vibration resistance		9 - 60 Hz, \pm 0.15 mm 5 - 9 Hz, \pm 3.5 mm 60 - 150 Hz, \pm 2 g
Air pressure		795 - 1080 hPa (operation)
Ambient operating temperature - min		0 °C
Ambient operating temperature - max		50 °C
Ambient storage temperature - min		-20 °C
Ambient storage temperature - max		60 °C
Climatic proofing		Cold to EN 60068-2-1 Dry heat to IEC 60068-2-2 Damp heat, constant, to IEC 60068-2-3
Environmental conditions		Condensation: Non-condensing
Operating temperature - min		0 °C
Operating temperature - max		50 °C
Relative humidity		10 - 95 % (non-condensing)
Emitted interference		According to IEC/EN 61000-6-4
Interference immunity		According to EN 61000-6-2
Voltage dips		\leq 10 ms from rated voltage (24 V DC) 5 ms from undervoltage (19.2 V DC)
Permissible voltage		19.2 - 30 V DC, effective (rated operating voltage -20 %/+25 %) 35 V DC (for a duration of < 100 ms) 18 - 31.2 V DC, battery powered (rated operating voltage -25 %/+30 %) 18.0 - 31.2 V DC, absolute with ripple
Power consumption		Max. 14.4 W 14 W typ.
Rated operational voltage		24 V DC (power-supply - safety extra low voltage)
Supply voltage at AC, 50 Hz - min		0 V AC
Supply voltage at AC, 50 Hz - max		0 V AC
Supply voltage at DC - min		19.2 V DC
Supply voltage at DC - max		30 V DC
Interfaces		CAN (not galvanically isolated, 9-pin SUB-D plug, UNC) 10/100 Mbps Ethernet connection RS232 (not galvanically isolated, 9-pin SUB-D plug, UNC) USB 2.0 host (not galvanically isolated) USB 2.0 device (not galvanically isolated) RS485 (not galvanically isolated, 9-pin SUB-D plug, UNC)
Number of slots		1 (for SD-Card)
Protocol		EtherNet/IP CAN MODBUS TCP/IP
Display contrast ratio		850:1
Display lighting		Dimmable via software

		LED
Display size		153.6 x 90.0 mm 16:9
Display type		TFT Anti-glare tempered glass in plastic bezel Color display, TFT, anti-glare
Luminance intensity		400 cd/m ²
Number of colors of the display		16777216
Resolution		1024 x 600 px WSVGA
Screen size (diagonal)		7 in
Touch technology		Projected Capacitive Touch (PCT) Capacitive multitouch Multi-touch touch panel touch sensor
Backup time		10 years, typ. (time at zero voltage)
Memory		Flash: 1 GByte SLC DRAM: 512 MByte RAM SD card, Type: SDSC, SDHC (external memory) NVRAM: 128kByte Retain
Memory capacity		512,000 kByte
Operating system		Windows Embedded Compact 7 Pro
Processor		ARM Cortex-A9 800 MHz
Equipment heat dissipation, current-dependent Pvid		14.4 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		14.4 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Graphic panel (EC001412)		
Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Graphic panel (HMI) (ecl@ss10.0.1-27-33-02-01 [AFX016003])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	19.2 - 30
Voltage type of supply voltage		DC

Number of HW-interfaces industrial Ethernet		2
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		1
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		2
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces other		1
With SW interfaces		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		No
Radio standard Bluetooth		No
Radio standard Wi-Fi 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
Type of display		TFT
With colour display		Yes
Number of colours of the display		16,777,216
Number of grey-scales/blue-scales of display		0
Screen diagonal	inch	7
Number of pixels, horizontal		1,024
Number of pixels, vertical		600
Useful project memory/user memory	kByte	512,000
With numeric keyboard		No
With alpha numeric keyboard		No
Number of function buttons, programmable		0
Number of buttons with LED		0
Number of system buttons		1
Touch technology		Capacitive multitouch
With message indication		Yes
With message system (incl. buffer and confirmation)		Yes

Process value representation (output) possible			Yes
Process default value (input) possible			Yes
With recipes			Yes
Number of password levels			200
With printer output			Yes
Number of online languages			100
Additional software components, loadable			Yes
Degree of protection (IP), front side			IP65
Degree of protection (NEMA), front side			12
Operating temperature		°C	0 - 50
Rail mounting possible			No
Wall mounting/direct mounting			No
Suitable for safety functions			No
Width of the front		mm	196
Height of the front		mm	135
Built-in depth		mm	43.1