

Touch panel - TP 6101-WXPS



1190417

<https://www.phoenixcontact.com/gb/products/1190417>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

IP66 Touch panel with 10.1-inch widescreen (16:9) XGA, PCAP display, software: Visu+ RT



Your advantages

- PCAP touch interface, ten-point multi touch control
- Fanless design
- Dual USB 2.0 ports
- Integrated Visu+ visualization software
- Ideal for use with PLCnext
- Configurable multifunction serial port

Commercial Data

Item number	1190417
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	DRCADC
Product Key	DRCADC
GTIN	4063151239176
Weight per Piece (including packing)	2,260 g
Weight per Piece (excluding packing)	2,100 g
Customs tariff number	84714100
Country of origin	TW

Touch panel - TP 6101-WXPS



1190417

<https://www.phoenixcontact.com/gb/products/1190417>

Technical Data

Product properties

Product type	Operator panel
--------------	----------------

Computer data

Processor	Arm® Cortex®-A9, 800 MHz
Operating system	Windows® Embedded Compact 7
Data storage	Flash eMMC, 8 GB
Slots	1x microSD

Display

Display type	25.9 cm / 10.2" TFT
Screen resolution	1280 x 800 Pixel(s) (WXGA)
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	500 cd/m² typical (adjustable)
MTBF	50000 h
Color spectrum	16.7 million colors
Reading angle left	85 °
Reading angle right	85 °
Reading angle top	85 °
Reading angle bottom	85 °

Software

User software	Visu+
---------------	-------

System requirements

Runtime system	Visu+ Runtime
----------------	---------------

Interfaces

Interfaces	2x USB Host 2.0 1x COM (RS-232/422/485)
Optional interfaces	Without optional interface
Network	1x Ethernet (10/100/1000 Mbps), RJ45
Bus system	without

Electrical properties

Supply

Supply voltage	24 V DC
Supply voltage range	18 V ... 32 V
Power supply unit	24 V DC ±20 %
Typical current consumption	0.79 A

Real-time clock

Touch panel - TP 6101-WXPS



1190417

<https://www.phoenixcontact.com/gb/products/1190417>

Realtime clock	Integrated (battery backup)
----------------	-----------------------------

Mounting

Mounting type	Front mounting
---------------	----------------

Material specifications

Material front plate	Aluminum (natural anodized)
Housing material	Aluminum cast alloy, powder-coated

Ambient conditions

Degree of protection	IP66 (front), IP20 (back)
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	5 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 85 % (non-condensing)
Vibration (operation)	1g

Dimensions

External dimensions

Width / Height / Depth	263 mm / 200 mm / 51 mm (Dimensions of the front plate)
------------------------	---

Installation dimensions

Width / Height / Installation depth	252 mm / 189 mm / (Installation cutout)
-------------------------------------	---

Touch panel - TP 6101-WXPS



1190417

<https://www.phoenixcontact.com/gb/products/1190417>

Approvals



EAC

Approval ID: RU C-DE.A*08.B01708



IECEE CB Scheme

Approval ID: US-39088-UL



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705

cULus Listed

Touch panel - TP 6101-WXPS



1190417

<https://www.phoenixcontact.com/gb/products/1190417>

Classifications

ECLASS

ECLASS-9.0	27330201
ECLASS-10.0.1	27330201
ECLASS-11.0	27330201

ETIM

ETIM 8.0	EC001412
----------	----------

UNSPSC

UNSPSC 21.0	43211900
-------------	----------

Touch panel - TP 6101-WXPS

1190417

<https://www.phoenixcontact.com/gb/products/1190417>



Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

Touch panel - TP 6101-WXPS

1190417

<https://www.phoenixcontact.com/gb/products/1190417>

Accessories

Panel-mount flange

Panel-mount flange - TP6/WP6/VL3 MOUNTING HW (2PCS) - 1289537

<https://www.phoenixcontact.com/gb/products/1289537>



Mounting kit includes two retaining clips

Battery

Battery - TP/WP 6000 RTC BATTERY KIT - 1289761

<https://www.phoenixcontact.com/gb/products/1289761>



Replacement battery for TP and WP 6000 touch panel

Touch panel - TP 6101-WXPS

1190417

<https://www.phoenixcontact.com/gb/products/1190417>

Memory

Memory - MICROSDHC-16GB - 1154696

<https://www.phoenixcontact.com/gb/products/1154696>



Industrial grade 16 GB MicroSDHC 3DTLC

Memory

Memory - MICROSDHC-32GB - 1154699

<https://www.phoenixcontact.com/gb/products/1154699>



Industrial grade 32 GB MicroSDHC 3DTLC

Touch panel - TP 6101-WXPS



1190417

<https://www.phoenixcontact.com/gb/products/1190417>

PCB connector

PCB connector - MSTB 2,5/ 3-STF-5,08 - 1777992

<https://www.phoenixcontact.com/gb/products/1777992>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Female connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTB 2,5/...-STF, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

Halesfield 13, Telford

Shropshire, TF7 4PG

01952 681700

info@phoenixcontact.co.uk