

Power Meter SICAM P55 Standard rail mounting 96 x 96 mm, type of protection front IP20, without graphic display 2 binary outputs, 2 analog inputs (DC 0-20 mA), RS485 with PROFIBUS DP and Modbus RTU / ASCII



Figure similar

Measuring functions	
sampling frequency / per sampling cycle	3 200 Hz
number of harmonics	19
product function / phase angle measurement	Yes
product function / active power measurement	Yes
product function / reactive power measurement	Yes
product function / apparent power measurement	Yes
product function / querying of limit violations	Yes
product function / logic function	Yes
product function / measurement of the harmonic active power	No
type of measured value detection / min./max. values	Yes
type of measured value detection / mean values	Yes
accuracy class / of the measuring instrument / for measured variable active power / according to IEC 62053-22	0,5S
accuracy class / of the measuring instrument / for measured variable reactive power	1
storage capacity	0.001 Gbyte
Power Quality functions	
power quality assessment function / transient detection/logging	No
power quality assessment function / Total Harmonic Distortion (THD)	Yes
power quality assessment function / voltage dip	No
power quality assessment function / measurement of the harmonic phase angle	No
product function / for voltage variations and flicker / integrated / according to IEC 61000-4-15	No
File formats	
type of data transmission / via CSV	No
Energy Management functions	
product function / active energy measurement	Yes
product function / reactive energy measurement	Yes
product function / apparent energy measurement	Yes
energy management function / calculation of load profiles	No
energy management function / tariffs	No
energy management function / load factor (TOU)	No
number of tariffs	0
Measuring inputs	
number of inputs / for voltage measurement	4
number of inputs / for current measurement	3
input voltage / between L and L / maximum	690 V

input voltage / between L and N / maximum	400 V
input current / maximum	10 A
<b>Supply voltage</b>	
supply voltage / at AC	110 ... 230 V
supply voltage / at DC	24 ... 250 V
measuring range frequency / at the measurement inputs	45 ... 65 Hz
type of voltage / of the supply voltage	AC/DC
<b>Inputs / Outputs</b>	
number of analog inputs	2
number of digital inputs	0
number of analog outputs	0
number of digital outputs	2
<b>Communication</b>	
protocol / is supported / IEC 61850	No
protocol / is supported / Modbus TCP	No
protocol / is supported / Modbus RTU	Yes
protocol / is supported / PROFIBUS DP	Yes
protocol / is supported / SNMP	No
protocol / is supported / OPC UA with PubSub	No
protocol / is supported / IEC 60870-5-103	No
communication function / Modbus RTU as master	No
number of ports / of the Ethernet interface	0
product function / gateway function for Modbus RTU	No
<b>Cybersecurity</b>	
type of access control / role-based access control (RBAC)	No
product function / logging via Audit log	No
product function / logging via Security Eventlog	No
service / as web server / HTTPS	No
product function / firmware identifier	No
<b>Time synchronization</b>	
type of time synchronization	RTC, Modbus RTU, binary input
<b>Mechanical Design</b>	
width	96 mm
height	96 mm
depth	105 mm
weight	650 g
product feature / with display	No
fastening method / standard rail mounting	Yes
fastening method / wall mounting	Yes
fastening method / rack mounting	No
type of electrical connection	Screw terminals
connectable conductor cross-section	2.5 mm <sup>2</sup>
<b>Degree of protection / protection class</b>	
protection class IP / on the front	IP20
protection class IP / rear side	IP20
<b>Environmental conditions</b>	
ambient temperature / during operation	-25 ... +55 °C
ambient temperature / during storage	-25 ... +70 °C
<b>Approval certification</b>	
certificate of suitability / CE marking	Yes
certificate of suitability / UL approval	No
<b>Further information</b>	

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information- and Downloadcenter (catalogues, leaflets,...)**

<http://www.siemens.com/energy-automation>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KG7755-0EA00-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7KG7755-0EA00-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=7KG7755-0EA00-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=7KG7755-0EA00-0AA0)

Tender specifications

<http://www.siemens.com/specifications>

---

